

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

Northeast Corner of Section 20
Township 145 N, Range 29 W, 5th P.M.
STATE OF MINNESOTA, COUNTY OF CASS



A000599925

OFFICE OF THE COUNTY RECORDER
CASS COUNTY, MINNESOTA
CERTIFIED, FILED, AND/OR
RECORDED ON

1/27/2014 10:38:36 AM

AS DOC #: A000599925

PAGES: 2

REC FEES: 0.00

KATHRYN M. NORBY
CASS COUNTY RECORDER

BY SR Dep


On _____, found a(n): _____

- left monument as found
- lowered monument
- removed monument (explain)
- raised monument

On 7/23/2012, set a(n): 5/8"x4' Rebar with 3.5" Aluminum Cap 1' Above Ground with a Fence Post on the North Side

See "Statement of Evidence" for further details (on back)

(reserved for recording data)



10" Poplar Nail & Disk In West Face Up 1.0' Set Tag



N 12° W
4.97'

5/8" x 4' Rebar With A 3.5" Aluminum Cap 1' Above Ground With A Fence Post On The North Side

S 39° W
31.55'

S 85° E
9.54'

8" Poplar Nail & Disk In North Face Up 1.0' Set Tag




7" Poplar Nail & Disk In Northwest Face Up 1.0' Set Tag



S 03° E
25.75'

12" Poplar Nail & Disk In West Face Up 1.0' Set Tag



"SKETCH OF REFERENCE TIES" (not to scale - bearings are magnetic)

Ties are measured to center of monument unless otherwise noted.

UNITS = Metric English

UTM COORDINATES, ZONE 15

Northing: 17214417.377

Easting: 1299919.022

NAD 83/1996 Adjustment.

Obtained by RTK GPS observations.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision, and that I am a duly Licensed Land Surveyor under the laws of the State of Minnesota.

Ross Wamre
signature

6/12/13
date

Ross Wamre, Minnesota License No. 45334



STATEMENT OF EVIDENCE: Section Corner common to Sections 16, 17, 20 and 21 of Township 145 North, Range 29 West of the 5th Principal Meridian.

1874; This corner was originally established by P. H. Conger, his field notes indicate that this corner was marked by a post and witnessed by:

- Black Pine 8" South 83° West, 83 links
- Black Pine 8" North 74° West, 81 links
- Black Pine 8" North 38° East, 115 links

1946; State of Minnesota Department of Highways Right-of-Way Map Index file 32-86 shows a Squared Wood Post in place with an angle of 79° 47' and distance of 1708.4' tie to U.S. Highway No. 2 at road station 695+24.7. Information on file with the Minnesota Department of Transportation.

2010; A Kadrmas, Lee & Jackson survey crew searched for this corner location and found no evidence.

2012; Ross Wamre, RLS #45334, after analysis of record and survey information set a 5/8" x 4' Rebar with 3.5" Aluminum Cap 1.0' above ground, at a calculated position from the field recovered alignment of U.S. Highway No. 2 using stationing, angle and distance according to State of Minnesota Department of Highways Right-of-Way Map Index file 32-86. Witnesses established as shown on face of this certificate.

Contacts pertaining to this corner are as follows:

- Cass County Recorder's Office
- Cass County Engineers Office
- Cass County Surveyors Office
- Northern Engineering and Consulting Inc.
- United States Forest Service
- MnDOT – District Office 2
- Bureau of Indians Affairs – Bemidji
- Bureau of Land Management's (BLM) Northeastern States Field Office