



A000600760

OFFICE OF THE COUNTY RECORDER  
CASS COUNTY, MINNESOTA  
CERTIFIED, FILED, AND/OR  
RECORDED ON

3/5/2014 11:19:12 AM

AS DOC #: A000600760

PAGES: 2

REC FEES: 0.00

KATHRYN M. NORBY  
CASS COUNTY RECORDER

BY SR \_\_\_\_\_ Dep

Twp 134 Rge 31 Index No. C.0-25.0

# CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

East Quarter corner of Section 1, Township 134 N., Range 31 W., 5th P.M.

State of Minnesota, County of Cass

At the corner location shown on the sketch:


On \_\_\_\_\_ found \_\_\_\_\_

left monument as found     lowered monument     removed monument (explain)

On 10 Jan 2014 placed a 1 inch by 30 inch aluminum tube with aluminum cap,  
up 1.0 foot, at toe of slope to the west.

Monument

SKETCH OF REFERENCE TIES  
NOT TO SCALE



is marked

Wooded

SECTION 1

Wooded  
SECTION 6

Wooded

Wooded

16d duplex nail  
up 1.0 feet in N side  
of 12 inch Red Oak

16d duplex nail  
up 1.0 feet in W. side  
of 6 inch Maple, tag

16d duplex nail  
up 1.0 feet in N. side  
of 6 inch Ash, tag

NE Cor  
Sec. 1

N 0°34'01" E 2633.76'

N 40° E  
14.50 feet

41.04 feet  
S 70° W

N 0°34'01" E 2633.75'

S 24°28' E  
51.28 feet

R31W

R30W

NE Cor.  
Sec. 12

NOTE:  
All bearings are true

Statement of evidence relative to this corner location is on the back of this page.

I hereby certify that this survey, plan or report was prepared by me or under my direct supervision and that I am a duly Licensed Land Surveyor under the laws of the State of Minnesota.

Terry L. Freeman, Cass County Surveyor

Date 3/5/14 MN License No. 21367



**Index No. C.0-25.0**

Statement of Evidence

**East Quarter corner of Section 1, Township 134 North, Range 31 West, 5th Principal Meridian.**

- May 1858 E.W. Darling, General Land Office (GLO) Deputy Surveyor in the survey of the east line of Twp.134 N., R.31 W. set a post for the original corner and referenced it as follows:  
5" W. Birch S 45° W 16 links (10.56 feet) 7" W. Birch N 37° E 14 links (9.24 feet)  
Said records are on file at the Minnesota Historical Society, St. Paul, Minnesota, copies are filed with the Cass County Highway Department, Surveyor's Office (CCHD/SO).
- Feb. 2008 B.Hippen CCHD/SO technician and P. Bundy resource manager, searched area for evidence of corner. Found no evidence of corner or witness trees.
- Jan. 2014 B.Hippen CCHD/SO technician and P. Bundy resource manager, set a 1 inch by 30 inch aluminum tube with aluminum cap, up 1.0 foot, midway and on line between the Northeast and Southeast corners of said Section 1 and witnessed as follows:  
6" Maple N 40° E 14.50 feet 12" R. Oak S 70° W 41.04 feet  
6" Ash S 51° E 24.28 feet

The monument, recovered and established references for the position are shown on the face of this document.

**Analysis of the recovered record data, field evidence and survey measurements, indicates that the monument set by the CCHD/SO is the accepted location of this corner.**

**County Coordinates (Cass County South)**

**Northing 206765.25**

**Easting 486826.82**