

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

East Quarter Corner of Section 27
Township 145 N , Range 27 W , 5th P.M.
STATE OF MINNESOTA, COUNTY OF CASS



A000600928

OFFICE OF THE COUNTY RECORDER
CASS COUNTY, MINNESOTA
CERTIFIED, FILED, AND/OR
RECORDED ON

3/13/2014 11:37:31 AM

AS DOC #: A000600928

PAGES: 3

REC FEES: 0.00

KATHRYN M. NORBY
CASS COUNTY RECORDER

BY SR Dep

On 05/19/2010 found a(n): 2" Iron Pipe With 3" Brass Cap
DATE
Stamped RLS# 3628

- left monument as found
- removed monument (explain)
- lowered monument
- raised monument

On _____, set a(n): _____
DATE

See "Statement of Evidence" for further details (on back)


(reserved for recording data)

2" Iron Pipe With
3" Brass Cap
Stamped RLS# 3628

8" Black Spruce, Nail
On East Face




12" Aspen With Bearing
Tag In Northeast Face



30" Red Pine
1958 BT Bearing
Tag in Northwest
Face

27 | 26



"SKETCH OF REFERENCE TIES" (not to scale - bearings are magnetic)

Ties are measured to center of monument
unless otherwise noted.

UNITS = Metric English

UTM COORDINATES, ZONE 15

Northing: 17205773.240

Easting: 1374565.751

NAD 83/1996 HARN Adjustment.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision, and that I am a duly Licensed Land Surveyor under the laws of the State of Minnesota.

Ross Wamre
signature

6/26/13
date

Ross Wamre, Minnesota License No. 45334



STATEMENT OF EVIDENCE: Quarter Corner common to Sections 26 and 27 of Township 145 North,
Range 27 West of the 5th Principal Meridian

1873; This corner was originally established by P.H. Conger for the GLO. His field notes indicate a post was set to mark this corner position which was witnessed by:

Jack Pine 4" South 81° West, 10 links
Jack Pine 10" North 65° East, 35 links

1924; H.K. Wright, USFS Forest Ranger, 874 forms, found a Jack Pine stake 4 feet high marked: ¼ S and witnessed. Information on file with the USFS office in Cass Lake.

Jack Pine Stump two feet high bearing B.T. in Section 26
Jack Pine 10" in Section 27
Jack Pine ridge, corner sets in old road

1936; USFS, 874 Forms, show a Jack Pine Stake witnessed. Information on file with the USFS office in Cass Lake.

Jack Pine Stump two feet high bearing B.T. in Section 26
Jack Pine 10" in Section 27

1958; Peter J. Meyer, RLS #3628, USFS Book 1 of Township 145 North, Range 27 West, page 10, found evidence of two remaining original bearing trees of the Government survey of 1873:

1873 Jack Pine 4" South 81° West, 10 links - now stump hole
1873 Jack Pine 10" North 65° East, 85 links - now a 12" stump partly decayed with scribing visible

Set 2" diameter 5' long galvanized wrought iron pipe filled with concrete and capped with a 3" stamped bronze tablet witnessed by:

White Pine 17" North 78° West, 86.1' - mkd. T145 R27 S27 BT
Red Pine 17" South 20 ½° West, 65.1' - mkd. T145 R27 S27 BT
Red Pine 16" South 49° East, 33.9' - mkd. T145 R27 S26 BT

Location Poster is on a 16" Red Pine from which the corner bears South 49° East 33.9' Blazed line North to road approx. 1200' tag on post on North side of road. An affidavit as to the location of the Government Corner is on file with Cass County Surveyor's Office.

2010; A Kadrmas, Lee & Jackson Survey Crew, found a 3" brass cap stamped RLS #3628, and evidence a 1958 BT as shown on the face of this certificate.

2012; Ross Wamre, RLS #45334, after analysis of record and survey information accepts this monument as the correct perpetuation of the corner.



Contacts pertaining to this corner are as follows:

Cass County Recorder's Office

Cass County Engineers Office

Cass County Surveyors Office

Northern Engineering and Consulting Inc.

United States Forest Service

MnDOT – District Office 2

Bureau of Indians Affairs – Bemidji

Bureau of Land Management's (BLM) Northeastern States Field Office