

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

East Quarter Corner of Section 36
Township 145 N, Range 27 W, 5th P.M.
STATE OF MINNESOTA, COUNTY OF CASS



A000601088

**OFFICE OF THE COUNTY RECORDER
CASS COUNTY, MINNESOTA
CERTIFIED, FILED, AND/OR
RECORDED ON**

3/20/2014 11:04:02 AM

AS DOC #: A000601088

PAGES: 2

REC FEES: 0.00

**KATHRYN M. NORBY
CASS COUNTY RECORDER**

BY SR Dep

On 05/19/2010, found a(n): 2" Steel Pipe With 3" Brass Cap
DATE
0.5' Above Ground, Stamped USFS 2001

- left monument as found
- lowered monument
- removed monument (explain)
- raised monument

On _____, set a(n): _____
DATE

See "Statement of Evidence" for further details (on back)

(reserved for recording data)


14" Red Pine With Existing Bearing Tag On South Face, 2001 BT

16" Red Pine Spike In South Face

18" Red Pine With Existing Bearing Tag On West Face, 2001 BT

2" Steel Pipe With 3" Brass Cap 0.5' Above Ground. Stamped USFS 2001

36 | 31



"SKETCH OF REFERENCE TIES" (not to scale - bearings are magnetic)

Ties are measured to center of monument unless otherwise noted.

UNITS = Metric English

UTM COORDINATES, ZONE 15

Northing: 17200196.350

Easting: 1384675.090

NAD 83/1996 HARN Adjustment.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision, and that I am a duly Licensed Land Surveyor under the laws of the State of Minnesota.

Ross Wamre
signature

6/25/13
date

Ross Wamre, Minnesota License No. 45334

Page 1 of 2 A000601088



STATEMENT OF EVIDENCE: Quarter Corner to Section 36 of Township 145 North, Range 27 West and Section 31 of Township 145 North, Range 26 West of the 5th Principal Meridian.

1873; This corner was originally established by P.H. Conger for the GLO. His field notes indicate that this corner position was marked with a post on the north edge of a swamp and witnessed by:

Norway Pine 6" North 61° West, 5 Links
Norway Pine 6" North 71° East, 82 Links

1933; USFS 874 form on file at the USFS office in Cass Lake, MN, shows that H.A. Brills, USFS, found a rotten wood stake at the ground line 24' above the ground, witnessed by:

Jack Pine 12" no bearing or distance
FSLP on section line 9.76 chains South of the corner

2001; John Tornes of MN DNR, Deer River reported he may have found an original BT with resource grade GPS and provided GPS location to USFS.

2001; USFS notes Book 2 of Township 145 North, Range 26 West, Page 33 show that Mike Hayes & Rob Main, USFS, found the original NW pine with rusted location tag. Brills in 1933 calls this a Jack Pine but bark appears to be Red Pine. Also found pine stump at bearing and distance for NE original. Hayes and Main scraped ground in a 3' x 3' area for post but no evidence found. From the two original bearing trees they set a 48" x 2" flared base galvanized pipe with Brass Tablet stamped USFS 2001. Corner is 10' east of swamp edge on west facing slope and 180' west of FR# 2272. Also found old tag on a plantation type post about 240' north of corner along FR# 2272. Monument is up 7" and witnessed by:

N. Pine Snag 14" North 61° West, 5 Links with ¼S scribing (1873 Tie)
N. Pine Stump 8" North 71° East, 82 Links with a visible scar (1873 Tie)
R. Pine 11.5" North 16° West, 15.18' scribed ¼ S36 BT
R. Pine 16" North 85° East, 16.2' scribed ¼ S31 BT

2010; A Kadrmas, Lee & Jackson survey crew found a 2" galvanized iron with a 3" Brass Cap stamped USFS 2001, 0.5' above ground in good condition, witnesses found and established as shown on the face of this certificate.

2012; Ross Wamre, RLS #45334, after analysis of record and survey information accepts this monument as the correct perpetuation of the corner.

Contacts pertaining to this corner are as follows:

Cass County Recorder's Office

Cass County Engineers Office

Cass County Surveyors Office

Northern Engineering and Consulting Inc.

United States Forest Service

MnDOT – District Office 2

Bureau of Indians Affairs – Bemidji

Bureau of Land Management's (BLM) Northeastern States Field Office