

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

North Quarter Corner of Section 17
Township 145 N, Range 30 W, 5th P.M.
STATE OF MINNESOTA, COUNTY OF Cass



A000601382

OFFICE OF THE COUNTY RECORDER
CASS COUNTY, MINNESOTA
CERTIFIED, FILED, AND/OR
RECORDED ON

4/3/2014 11:29:53 AM

AS DOC #: A000601382

PAGES: 2

REC FEES: 0.00

KATHRYN M. NORBY
CASS COUNTY RECORDER

BY SR Dep

On 4/22/2010, found a(n): 2" Aluminum GLO Disc
marked 1933. 1' above the ground.
BRASS


- left monument as found
- lowered monument
- removed monument (explain)
- raised monument

On _____, set a(n): _____

See "Statement of Evidence" for further details (on back)

(reserved for recording data)


18" White Pine Set Spike
and Plastic Disc in the
West face with 1933
USFS shield tag 54-3
marked: S 32 E 36 lks



Norway Beach
Campsite # 108

GLO Brass Cap On
A 2" Iron Pipe


N 32° W
23.76'



15" Norway Pine
Set Spike and
Plastic Disc in the
SE face Set tag


N 43° E
19.57'

12" Norway Pine Set Spike
and Plastic Disc in the West
face Existing FSLP tag 54-6
marked: L.M. 12-1970
(No Record Of This Being Set)



S 20° W
9.66'

14" Norway Pine Set
Spike and Plastic Disc
in the NE face Set tag




S 49° E
20.59'

8

17

"SKETCH OF REFERENCE TIES" (not to scale - bearings are magnetic)



Ties are measured to center of monument
unless otherwise noted.

UNITS = Metric English

UTM COORDINATES, ZONE 15

Northing: 17220253.784

Easting: 1266088.112

NAD 83/1996 Adjustment.

Obtained by RTK GPS observations.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision, and that I am a duly Licensed Land Surveyor under the laws of the State of Minnesota.

Ross Wamre
signature

7/8/13
date

Ross Wamre, Minnesota License No. 45334





STATEMENT OF EVIDENCE: Quarter Corner common to Sections 8 and 17 of Township 145 North,
Range 30 West of the 5th Principal Meridian

1874; This corner was originally established by P.H. Conger for the GLO. His field notes indicate a wood post set at this corner position, witnessed by:

Yellow Pine 20" South 7^o West, 4 Links
Yellow Pine 20" North 4^o West, 30 Links

1933; Resurvey by GLO, Willis W. Bandy from remains of original bearing trees, set a 2" diameter, 36" iron post with a stamped brass cap witnessed by:

Norway Pine Stump 24" South 7^o West, 4 Links – mkd. B.T. (1874 Tie)
Norway Pine 24" North 4 $\frac{3}{4}$ ^o West, 30 Links – mkd. B.T. (1874 Tie)
White Pine 6" North 32^o West, 36 Links
Norway Pine 24" South $\frac{1}{2}$ ^o West, 78 Links

1934; USFS 874 form, on file at the USFS office in Cass Lake, MN show J.A. Gjelhaug, RLS #1337, found a 1 $\frac{1}{2}$ " stamped brass capped iron pipe 6" above the ground witnessed by:

White Pine 6" North 32 $\frac{1}{2}$ ^o West, 36 $\frac{1}{4}$ Links marked: " $\frac{1}{4}$ S8 BT" (1933 Tie)
Norway Pine 20" South, 75 $\frac{1}{4}$ Links marked: " $\frac{1}{4}$ S17 BT" (1933 Tie)

2010; A Kadrmas, Lee & Jackson survey crew found a 2" Brass Capped Standard GLO Iron Pipe stamped 1933, 1' above ground, witnesses found and established as shown on the face of this certificate.

2012; Ross Wamre, RLS #45334, after analysis of record and survey information accepts this monument as the correct perpetuation of the corner.

Contacts pertaining to this corner are as follows:

Cass County Recorder's Office

Cass County Engineers Office

Cass County Surveyors Office

Northern Engineering and Consulting Inc.

United States Forest Service

MnDOT – District Office 2

Bureau of Indians Affairs – Bemidji

Bureau of Land Management's (BLM) Northeastern States Field Office