

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

North Quarter Corner of Section 20
Township 145 N , Range 30 W , 5th P.M.
STATE OF MINNESOTA, COUNTY OF CASS



A000601390

OFFICE OF THE COUNTY RECORDER
CASS COUNTY, MINNESOTA
CERTIFIED, FILED, AND/OR
RECORDED ON

4/3/2014 11:30:01 AM

AS DOC #: A000601390

PAGES: 2

REC FEES: 0.00

KATHRYN M. NORBY
CASS COUNTY RECORDER

BY SR Dep

On 04/15/2010, found a(n): 2" Iron Post with a 2" Brass
DATE
cap stamped 1933, Aprox. 1.0' Above Ground

- left monument as found
- lowered monument
- removed monument (explain)
- raised monument

On _____, set a(n): _____
DATE

See "Statement of Evidence" for further details (on back)

(reserved for recording data)

7" Oak
Alum. tag SE face
Spike in south face



N 60° W
12.70'

2" Iron Post with 2" Brass
Cap stamped 1933, Aprox. 1.0'
Above Ground


8" Oak
Alum. tag NE face
Spike in west face



S 7° W
35.70'

S 7° E
125.50'

18" Red Pine
Alum. tag NW face
Spike set in east face



17

20

"SKETCH OF REFERENCE TIES" (not to scale - bearings are magnetic)

Ties are measured to center of monument unless otherwise noted.

UNITS = Metric English

UTM COORDINATES, ZONE 15

Northing: 17214941.900

Easting: 1266.098.842

NAD 83/1996 Adjustment.

Obtained by RTK GPS observations.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision, and that I am a duly Licensed Land Surveyor under the laws of the State of Minnesota.

Ross Wamre
signature

7/8/13
date

Ross Wamre, Minnesota License No. 45334





STATEMENT OF EVIDENCE: Quarter Corner common to Sections 17 and 20 of Township 145 North, Range 30 West of the 5th Principal Meridian

1874; This corner was originally established by P.H. Conger for the GLO. His field notes indicate this corner position, witnessed by:

Yellow Pine 18" North 33^o East, 20 links
Black Oak 3" South 50^o East, 53 links

1933; Resurvey by GLO, Willis W. Bandy, as determined from the remains of the original bearing trees, set a 2" diameter 3' long iron post with stamped Brass Cap witnessed by:

Dead Norway Pine 20" North 33^o East, 20 links mkd. ¼ S B.T. (1874 Tie)
Red Oak Stump South 54^o East, 53 links no visible marks (1874 Tie)
Norway Pine 8" North 1^o West, 12 links
Norway Pine 6" South 36¾^o East, 16 links

1934; J.A. Gjelhaug, CCC, RLS# 1337, USFS 874 forms, found a 1 ½" Capped Iron Pipe 6" above ground, witnessed. Information on file with the USFS office in Cass Lake.

N. Pine 8" North 3^o West, 11 ¼ links, mrkd ¼ S 17 BT (1933 tie)
N. Pine 6" South 38^o East, 15 ½ links, mrkd ¼ S 20 BT (1933 tie)

1966; William H. Okerman, RLS #6807 and James Ebstrom, USFS Book 2 of Township 145 North, Range 30 West, page 28, found monument in place along with GLO bearing trees. An Affidavit as to Location of Government Corner is on file at the Cass County Office of Register of Deeds. Corner is witnessed by:

Dead Norway Pine 20" North 33^o East, 20 links mkd. ¼ S B.T. (1874 Tie)
Red Oak Stump South 54^o East, 53 links no visible marks (1874 Tie)
N. Pine 13" North 1^o West, 7.92 ft., scribe visible (1933 tie)
N. Pine 14" South 36^o East, 10.56 ft., re-scribed visible (1933 tie)

1990; C. Krause, USFS Book 2 of Township 145 North, Range 30 West, page 28, found remains of original BT's, did not tie corner.

2010; A Kadrmas, Lee & Jackson survey crew found a 2" Iron Post with a 2" Brass Cap Standard GLO monument stamped 1933, approximately 1.0' above ground. Witnesses established as shown on the front of this certificate.

2012; Ross Wamre, RLS #45334, after analysis of record and survey information accepts this monument as the correct perpetuation of the corner.

Contacts pertaining to this corner are as follows:

Cass County Recorder's Office	Cass County Engineers Office
Cass County Surveyors Office	Northern Engineering and Consulting Inc.
United States Forest Service	MnDOT – District Office 2
Bureau of Land Management's (BLM) Northeastern States Field Office	