CERTIFICATE OF LOCATION OF GOVERNMENT CORNER East Quarter	A000601397 OFFICE OF THE COUNTY RECORDER CASS COUNTY, MINNESOTA CERTIFIED, FILED, AND/OR RECORDED ON 4/3/2014 11:30:08 AM AS DOC #: A000601397 PAGES: 3 REC FEES: 0.00 KATHRYN M. NORBY CASS COUNTY RECORDER BY SR Dep
See "Statement of Evidence" for further details (on back)	(reserved for recording data)
the South face set in 2002, FSLP of tag 458-A marked: "GJ & CS of B	6" Birch set Spike and Plastic pisc on the South face set tag
18" Norway Pine Con	
"SKETCH OF REFERENCE TIES" (not to scale — bearings are magnetic) Ties are measured to center of monument unless otherwise noted. UNITS = Metric English	Northing: 172 18 59 4 000601397 NAD 83/1996 Adjustment: Obtained by RTK GPS observations
I hereby certify that this survey, plan, or report was prepared by me I am a duly Licensed Land Surveyor under the laws of the	

Ross Wamre, Minnesota License No. 45334



Page 2 of 3 A000601397

STATEMENT OF EVIDENCE: Quarter Corner common to Sections 17 and 18 of Township 145 North, Range 30 West of the 5th Principal Meridian

1874; This corner was originally established by P.H. Conger for the GLO. His field notes indicate a wood post set at this corner position, witnessed by:

Yellow Pine 20" South 37° East, 18 Links Yellow Pine 24" North 82° West, 6 Links

- 1911; Railroad Right of Way Map 1141CS3 shows an angle and distance tie to this corner location. Information is on file with the Minnesota Department of Transportation.
- 1933; Resurvey by GLO, Willis W. Bandy from remains of original bearing trees, set a 36" iron post in concrete with a 3 ½" diameter stamped brass cap witnessed by:

Norway Pine 27" North 20¾° East, 72.20'

- **1946**; MNDOT Right of Way Map 32-86 shows a Brass Cap set in Concrete in place at this corner location. Information is on file with the Minnesota Department of Transportation.
- 1966; USFS notes of Township 145 North, Range 30 West, Book2, Page 12, on file at the USFS office in Cass Lake, MN show James Ebstrom, USFS, found a 3 ½" brass cap set in 6" dia. of cement in good condition witnessed by:

Norway Pine 26" North 20° East, 79.20' scribe visible (1933 Tie) White Pine 9" South 19° West, 53.4' scribed "¼ S18 BT" Norway Pine 9" South 71° West, 35.6' scribed "¼ S18 BT"

1997; USFS notes of Township 145 North, Range 30 West, Book2, Page 12, on file at the USFS office in Cass Lake, MN show Bill Ausk, USFS, found the monument in place witnessed by:

Broken Off Norway Pine 26" North 20° East, 79.20' (1933 Tie) White Pine 9" South 19° West, 53.4' (1966 Tie) Norway Pine 9" South 71° West, 35.6' (1966 Tie)

2002; USFS notes of Township 145 North, Range 30 West, Book2, Page 12, on file at the USFS office in Cass Lake, MN show R. Main, USFS, found the monument in place flush with the ground. The corner is 40' West of Norway Beach hiking trail witnessed by:

Norway Pine with Top Broken Off 30" North 20° East, 79.20' (1933 Tie)
White Pine 24" South 19° West, 53.4' (1966 Tie)
Norway Pine 17" South 71° West, 35.6' (1966 Tie)
Set Spike on S Face of Red Pine 31" North 74° West, 4.12' existing tag marked: "GJ & CS 3-29-62"

2010; A Kadrmas, Lee & Jackson survey crew found a 6" concrete monument with a 3.5" brass capped standard GLO monument stamped 1933, 1' above ground, 40' West of a trail, witnesses found and established as shown on face of this certificate.



Page 3 of 3 A000601397

2012; Ross Wamre, RLS #45334, after analysis of record and survey information accepts this monument as the correct perpetuation of the corner.

Contacts pertaining to this corner are as follows:
Cass County Recorder's Office
Cass County Engineers Office
Cass County Surveyors Office
Northern Engineering and Consulting Inc.
United States Forest Service
MnDOT – District Office 2
Bureau of Indians Affairs – Bemidji
Bureau of Land Management's (BLM) Northeastern States Field Office