



A000601710

OFFICE OF THE COUNTY RECORDER
 CASS COUNTY, MINNESOTA
 CERTIFIED, FILED, AND/OR
 RECORDED ON

4/17/2014 11:13:20 AM

AS DOC #: A000601710

PAGES: 2

REC FEES: 0.00

KATHRYN M. NORBY
 CASS COUNTY RECORDER

BY SR Dep

Index No. N-13

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

Northeast Corner of Section 21
 Township 145 N, Range 30 W, 5th P.M.
 STATE OF MINNESOTA, COUNTY OF CASS

On 04/14/2010, found a(n): 6" concrete monument with a
DATE
3.5" Brass cap stamped 1933, 1.0' Above Ground

- left monument as found lowered monument
 removed monument (explain) raised monument

On _____, set a(n): _____
DATE

See "Statement of Evidence" for further details (on back)

(reserved for recording data)

22" Oak
 Alum. tag SE face
 Spike in north face



N 80° W
 60.30'

6" concrete monument 3.5"
 Brass Cap stamped 1933, 1.0'
 Above Ground

1933, 36" Red Oak
 Alum. tag NW face
 Spike in south face



S 71° E
 50.20'

1966, 20" Burr Oak
 Alum. tag NE face
 Spike in east face



S 11° W
 59.00'

16 | 15

21 | 22

"SKETCH OF REFERENCE TIES" (not to scale - bearings are magnetic)



Ties are measured to center of monument
 unless otherwise noted.

UNITS = Metric English

UTM COORDINATES, ZONE 15

Northing: 17214629.200

Easting: 1273970.541

NAD 83/1996 Adjustment.

Obtained by RTK GPS observations.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision, and that I am a duly Licensed Land Surveyor under the laws of the State of Minnesota.

Ross Wamre
 signature

4/7/14
 date

Ross Wamre, Minnesota License No. 45334



STATEMENT OF EVIDENCE: Corner common to Sections 15, 16, 21 and 22 of Township 145 North, Range 30 West of the 5th Principal Meridian

1874; This corner was originally established by P.H. Conger his field notes indicate this corner position, witnessed by:

- White Pine 30" North 48° West, 64 links
- White Pine 30" South 10° East, 70 links
- White Pine 24" South 45° West, 80 links

1916; Railroad Valuation Map 1804CS2. Minneapolis St. Paul & Sioux St. Marie Railway Company's Right of Way and Track Maps shows a distance tie to the railroad from this corner. Information on file with the Minnesota Department of Transportation.

1933; Resurvey by GLO, Willis W. Bandy, set a 6" diameter 2' long cylindrical concrete monument, 20" in the ground, with a 3.5" Brass Cap stamped 1933 and witnessed by:

- Down Norway Pine 48" South 45° West, 80 Links old blaze & dim scribe marks (1874 Tie)
- Charred White Pine snag South 10° East, 70 Links (1874 Tie)

New BT:

- Burr Oak 8" North 51 ¼° East, 99 links (65.34')
- Red Oak 14" South 71 ¼° East, 76 links (50.16')
- Burr Oak 6" South 14 ¾° West, 113 links (74.58')
- Burr Oak 6" North 32° West, 102 links (67.32')

1934; J.A. Gjelhaug, CCC, LS# 1337, USFS 874 forms, found a 5" Brass Cap in Cement 8" above ground and witnessed. Information on file with the USFS office in Cass Lake.

- Red (Burr) Oak 10" North 51° East, 98 links (1933 tie) mrkd S 15 BT
- Red Oak 12" South 72° East, 75 ¼ links (1933 tie) mrkd S 22 BT
- Red (Burr) Oak 6" South 7° West, 111 links (1933 tie) mrkd S 21 BT
- Red (Burr) Oak 14" North 33° West, 101 links (1933 tie) mrkd S 16 BT
- Aspen 3" South 10° East, 10 Links with Metal Poster

1946; State of Minnesota Department of Highways Right-of-Way Index map file 32-86 shows a Brass Cap Set in Concrete in place at this corner location. Information on file with the USFS office in Cass Lake.

1966; William H. Okerman, RLS #6807 and Milton Hansey, USFS Book 2 of Township 30 North, Range 30 West, page 30, found monument in good condition and two of the GLO 1933 BTs. An Affidavit as to Location of Government Corner is on file at the Cass County Office of Register of Deeds. Corner is witnessed by:

- Red Oak 21" South 71° East, 50.2'(1933 tie) re-scribed
- Burr Oak (stump) South 14 ¾° West, 113 links - 74.58' with scribe (1933 tie)
- Burr Oak 16" North 32° West, 67.3'(1933 tie) re-scribed

New BT:

- Burr Oak 9" South 11° West, 59.0' scribed S 21 BT
- Burr Oak 9" North 81° East, 27.85' scribed S 15 BT

2010; A Kadrmas, Lee & Jackson survey crew found a 6" concrete monument with a 3.5" Brass Cap Standard GLO Monument, 1933, 1.0' above ground. Witnesses found and established as shown on the face of this certificate.

2012; Ross Wamre, RLS #45334, after analysis of record and survey information accepts this monument as the correct perpetuation of the corner.

Contacts pertaining to this corner are as follows:

- | | |
|--|--|
| Cass County Recorder's Office | Cass County Engineers Office |
| Cass County Surveyors Office | Northern Engineering and Consulting Inc. |
| United States Forest Service | MnDOT – District Office 2 |
| Bureau of Indians Affairs – Bemidji | |
| Bureau of Land Management's (BLM) Northeastern States Field Office | |