## CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

At the comer location s On  Date  left monument as	hown on the sketch:found a	lowered monumer	nt rem	e of Minnesota, County of  Cass  oved monument (explain)
		SKETCH OF REF	ERENCE TIES	Tie Distances are measured to the spikes.  Cass County Coordinate System (South Zone)
Sec. 29  N88°14'27"E 5238.90  NE Cor.	NE Cor. Sec. 32	N88*09'58'E 5238.90		N= 309865.0811 E= 461669.2613  o Set Re-Rod with RLS cap No. 17774  • Found Pipe
Sec. 31		pike on South de 16" Poplar Sec	<b>:. 33</b>	
Spike on West side twin 12" M	SE Cor. Sec. 31			OFFICE OF COUNTY RECORDER

## **NOT TO SCALE**

Statement of evidence relative to this corner location is on back of page.

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

Maryin R. Kohout

Amended 18 June 2014

Registration No, 17774

Amended 12 Aug 2014

Land surveyor

Page 1 of 2



## A000604901

OFFICE OF THE COUNTY RECORDER CASS COUNTY, MINNESOTA CERTIFIED, FILED, AND/OR RECORDED ON

8/20/2014 11:22:46 AM

AS DOC #: A000604901

PAGES: 2 REC FEES: 0.00

KATHRYN M. NORBY CASS COUNTY RECORDER

BY\_SR\_\_\_Dep

Page 2 of 2 A000604901

INDEX NO. V.0 - 9.0

## STATEMENT OF EVIDENCE

NORTHEAST CORNER SECTION 32, TOWNSHIP 138N, RANGE 31W, 5<sup>TH</sup> P.M.

NOV. T.B. WALKER, GENERAL LAND OFFICE (GLO) DEPUTY SURVEYOR SET A POST 1870 AND MARKED B.T.'S. REFERENCES ARE:

4" RED OAK	4" WHITE PINE	4" WHITE PINE	6" BIRCH
S 79 E	N 231/2 E	S 59 W	N 461/2 W
4 LKS	18 LKS	10 LKS	20 LKS

- OCT. J.A. JOHNSTON, CASS COUNTY, STATES "AT CHAINAGE 5280' WE LOOK 1915 CAREFULLY FOR SECTION CORNER, BUT NO SIGN OF BEARING TREES COULD BE FOUND, COUNTRY HIGH AND BADLY BURNED. SMALL PINE HERE WERE CUT FOR TIMBER ABOUT SEVEN YEARS AGO (ACCORDING TO INFORMATION RECEIVED FROM KINNEY AND M. WAHLQUIST) SURVEY RECORD NO. 365 **BOOK B PAGE 587**
- AUG. B. HIPPEN, CCSO TECHNICIAN, RECORDS OF CCSO, MADE A SEARCH AT THIS 2006 POSITION AND FOUND A PINE STUMP WITH A SMALL WINDOW ON THE SOUTH WEST SIDE. THIS POSITION FITS WELL WITH LAND CALLS
- 2012 MARVIN KOHOUT, LS NO. 17774, AND DOUG STILLE, TECHNICIAN, OF KOHOUT LAND SURVEYING, SEARCHED FOR EVIDENCE OF THIS CORNER, NOTHING FOUND. A 3/8" DIA. REROD WITH RLS CAP NO.17774 WAS SET MIDWAY BETWEEN THE SE CORNER OF SECTION 32 AND THE NE CORNER OF SECTION 29 AND MIDWAY BETWEEN THE NE CORNER OF SECTION 31 AND THE NE CORNER OF SECTION 33.