



A000607945

OFFICE OF THE COUNTY RECORDER  
CASS COUNTY, MINNESOTA  
CERTIFIED, FILED, AND/OR  
RECORDED ON

12/4/2014 1:17:40 PM

AS DOC #: A000607945

PAGES: 2

REC FEES: 0.00

KATHRYN M. NORBY  
CASS COUNTY RECORDER

BY SR \_\_\_\_\_ Dep

Twp 143 Rge 27 Index No. A.0-23.0

### CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

North Quarter corner of Section 1, Township 143 N., Range 27 W., 5th P.M.  
State of Minnesota, County of Cass

At the corner location shown on the sketch:


On 11 Feb 2009 found a 1 inch outside diameter iron pipe with brass cap,  
up 0.8 foot, in Tamarack Swamp.

left monument as found     lowered monument     removed monument (explain)

On \_\_\_\_\_ placed \_\_\_\_\_


Monument

SKETCH OF REFERENCE TIES  
NOT TO SCALE




is marked

16d duplex nail  
up 1.0 foot in N side  
of 6 inch Tamarack




16d duplex nail  
up 1.0 foot in S side  
of 6 inch Tamarack



Tamarack Swamp

SECTION 36

Old Stump  
(1937)



T 144 N  
T 143 N

SECTION 1

Tamarack Swamp



16d duplex nail  
up 1.0 foot in W side  
of 8 inch Tamarack

NOTE:  
All bearings are true

Statement of evidence relative to this corner location is on the back of this page.

I hereby certify that this survey, plan or report was prepared by me or under my direct supervision and that I am a duly Licensed Land Surveyor under the laws of the State of Minnesota.

Terry L. Freeman, Cass County Surveyor

Date 12/3/14 MN License No. 21367



**Index No. A.0-23.0**Statement of Evidence**North Quarter corner of Section 1, Township 143 North, Range 27 West, 5th Principal Meridian.**

- July 1873 P.H. Conger, General Land Office (GLO) Deputy Surveyor notes of the subdivision of Township 143 North, Range 27 West, set a post for the original corner and referenced it as follows:  
 12" Tamarack S 75° E 23 links (15.18 feet) 5" Tamarack N 40° W 13 links (8.58 feet)  
 The above record is on file with the Minnesota Historical Society in St. Paul, Minnesota, copies are filed with the Cass County Highway Department, Surveyor's Office (CCHD/SO).
- April 1900 F.V. Abbot, Major, United States Army, Corps of Engineers (COE), Lake Pokegama Reservoir Map 143-27, on file with the United States Department of Agriculture, Forest Service (USFS) offices in Cass Lake, MN, by symbol indicates this to be a known corner. Book A1-235, page 34, indicates found both BT's. standing with blaze, Old post found in place.
- July 1937 H.D. Craig, U. S. Surveyor, GLO, Dependent Resurvey of Township 144 North, Range 27 West, on file with the Minnesota Historical Society, St. Paul, Minnesota, copies are filed with the CCHD/SO, states "Proportionate distance; there is no remaining evidence of the original 1/4 sec. cor. Set an iron post, 3 ft. long, 1 ins. diam., 28 ins. in the ground, for 1/4 sec. cor. with brass cap" and lists new witnesses as follows:  
 6" Cedar N 33 1/2° E 33 links (21.78 feet) 6" Tamarack S 86 3/4° W 27 links (17.82 feet)
- 1960 USFS, Field Book #2, page 41, on file in the offices in Cass Lake, MN, notes only indicates the original GLO and 1937 GLO witnesses and 1900 COE information.
- Feb. 2009 B. Hippen, technician, records of the CCHD/SO, found the 1937 GLO 1 inch iron pipe with brass cap, up 0.8 foot in Tamarack swamp and witnessed it as follows:  
 Tamarack stump S 87° W 18 feet (1937) 8" Tamarack S 20° E 23.31 feet  
 6" Tamarack N 45° E 20.47 feet 6" Tamarack N 61° W 6.57 feet  
 The recovered and established references for the position are shown on the face of this document.

**Analysis of the recovered record data, field evidence and survey measurements, indicates that the monument recovered by the CCHD/SO in 2009 is the accepted location for this corner.**

**County Coordinates (Cass County North)**

**The post process session failed.**