



A000608287

OFFICE OF THE COUNTY RECORDER  
CASS COUNTY, MINNESOTA  
CERTIFIED, FILED, AND/OR  
RECORDED ON

12/18/2014 10:49:11 AM

AS DOC #: A000608287

PAGES: 2

REC FEES: 0.00

KATHRYN M. NORBY  
CASS COUNTY RECORDER

BY SR \_\_\_\_\_ Dep

Twp 142 Rge 27 Index No. C.0-06.0

### CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

CW Sixteenth corner of Section 5, Township 142 N., Range 27 W., 5th P.M.  
State of Minnesota, County of Cass

At the corner location shown on the sketch:


On 26 June 2009 found a 1 inch outside diameter iron pipe with GLO brass cap,  
up 0.5 foot.

left monument as found     lowered monument     removed monument (explain)

On \_\_\_\_\_ placed \_\_\_\_\_

Monument

SKETCH OF REFERENCE TIES  
NOT TO SCALE



is marked



60d spike (1993)  
up 0.4 foot in S side  
of 12 inch Burr Oak

Wooded

60d spike (1993)  
up 0.5 foot in S side  
of 14 inch Burr Oak

68.45 feet  
N 49° W

69.00 feet  
N 71° E

3.1' □

USFS Steel  
Sign Post

SECTION 5

Old Field

NOTE:

All bearings are true

Statement of evidence relative to this corner location is on the back of this page.

I hereby certify that this survey, plan or report was prepared by me or under my direct supervision and that I am a duly Licensed Land Surveyor under the laws of the State of Minnesota.

Terry L. Freeman, Cass County Surveyor

Date 12/17/14 MN License No. 21367





**Index No. C.0-06.0**

Statement of Evidence

**Center West One Sixteenth corner Section 5, Township 142 North, Range 27 West, 5th Principal Meridian.**

- 1920 E.G. Harrington, U.S. Cadastral Engineer, assisted by D.B. Clement, U.S. Surveyor, GLO, Reestablishment of a portion of the Exteriors and Subdivisional Lines Township 142 North, Range 27 West, on file with the Minnesota Historical Society in St. Paul, Minnesota, copies are filed with the CCHD/SO, states "Set an iron post, 3 ft. long, 1 ins. diam., 26 ins. in the ground, for the C.W. 1/16 sec. cor. with brass cap". Lists the following witnesses:  
10" Cedar N 70 3/4° E 46 links(30.36 feet) 8" Cedar N 85 1/2° W 40 links (26.40 feet)
- March 1993 R. Main, technician, United States Department of Agriculture Forest Service (USFS), T 142N R 27 W Book 3, page 4, on file in the USFS Cass Lake Office, states Found GLO iron, up 2 feet and witnessed as follows:  
14" W. Oak N 71° E 69.00 feet 12" W. Oak N 49° W 68.45 feet
- June 2009 B. Hippen, technician, records of the CCHD/SO, found 1 inch outside diameter iron pipe, with GLO brass cap, up 0.5 foot and 1993 witnesses, also the following:  
Steel Sign Post East 3.1 feet

The monument, recovered and established references for the position are shown on the face of this document.

**Analysis of the recovered record data, field evidence and survey measurements, indicates that the monument recovered by CCHD/SO in 2009 is the accepted location of this corner.**

**County Coordinates (Cass County North)**

**Northing 225002.12**  
**Easting 521119.72**