CEPTIFICATE OF LOCATION OF COVERNMENT CORNER


e corner location shown on the sketch: Onfound a		
Date		
left monument as found	lowered monument	removed monument (explain)
On 19 JAN. 2015 placed a	3/8" DIAMETER REROD WITH RLS CAP NO. 17774	
	SKETCH OF REFERENCE	E TIES

SEC. 35 T. 141 N. R.26 W. SPIKE IN 5" ASH N78°36'21"E SPIKE IN 8" ASH 146 +/-N88°58'01"W 137.42 WITNESS CORNER 10TH STANDARD PARALLEL T. 140 N. SEC. R.26 W.

Cass County Coordinate System (North Zone) MC #1 N= 163343.66 E= 569815.02 Wit.Cor. N= 163340.14 E= 570009.44

Set Re-Rod with RLS cap No. 17774

Found Pipe



NOT TO SCALE

Statement of evidence relative to this corner location is on back of page.

SPIKE IN 6" ASH

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

Mawink Kohout Marvin R. Kollout

Date

License No, <u>17</u>

Land surveyor

Page 1 of 2

OFFICE OF COUNTY RECORDER



OFFICE OF THE COUNTY RECORDER CASS COUNTY, MINNESOTA CERTIFIED, FILED, AND/OR **RECORDED ON**

2/19/2015 10:51:00 AM

AS DOC #: A000609681

PAGES: **REC FEES: 0.00**

KATHRYN M. NORBY CASS COUNTY RECORDER

BY SR Dep TX#: 121129



Page 2 of 2 A00

INDEX NO. Z.0-18.3

STATEMENT OF EVIDENCE

MEANDER CORNER NO. 1 OF SECTION 35, TOWNSHIP 141N, RANGE 26W, 5TH P.M.

- 1863 G. JOHNSON AND A. THORNTON, DEPUTY GOVERNMENT SURVEYORS, SET A POST TO MARK THE CORNER LOCATION. REFERENCES:
 - 8" WILLOW N72E 10.56 FT
 - 8" WILLOW N50W 30.36 FT
 - RECORDS ON FILE AT THE MN HISTORICAL SOCIETY, ST. PAUL, AND COPIES FILED WITH CASS COUNTY HIGHWAY DEPT/SURVEYOR'S OFFICE (CCHD/SO)
- 1912 HARRY S. TODD SEARCHED FOR EVIDENCE OF THIS CORNER FOUND NOTHING. CURO BOOK 93 PAGES 40-42 CCHD/SO
- 2014 MARVIN KOHOUT, LS NO 17774, KOHOUT LAND SURVEYING, SEARCHED FOR EVIDENCE OF THIS CORNER. FINDING NONE, A 3/8" DIAMETER REROD WITH RLS CAP NO. 17774 WAS COMPUTED AT A PROPORTIONATE DISTANCE AND ON LINE BETWEEN THE SE CORNER OF SEC. 35 AND THE POSITION OF MC #3 AS SHOWN ON CERTIFICATE OF GOVT CORNER LOCATION DOC. NO. 597188. COMPUTED POSITION FALLS IN LAKE, SET A WITNESS CORNER 194.46 FEET EASTERLY. REFERENCES AS SHOWN ON PAGE 1

PAGE 2 OF 2 PAGES