

OFFICE OF THE COUNTY RECORDER CASS COUNTY, MINNESOTA CERTIFIED, FILED, AND/OR RECORDED ON

12/17/2015 12:21:55 PM AS DOC #: A000618128 PAGES: 2 REC FEES: 0.00

KATHRYN M. NORBY CASS COUNTY RECORDER

BY_SR__Dep TX#: 127883

Twp <u>143</u> Rge <u>26</u> Index No. <u>V.0-03.0</u>
CERTIFICATE OF LOCATION OF GOVERNMENT CORNER
North Quarter corner of Section 31 ,Township 143 N. ,Range 26 W. , 5th P.M.
State of Minnesota, County of Cass
At the corner location shown on the sketch:
On 5 Aug 2015 found a 2.5 inch iron pipe with brass cap, down 0.1 foot,
58 feet± north of centerline County Road #4.
On placed
Monument SKETCH OF REFERENCE TIES
NOT TO SCALE
T143N R26W Yard
$ \begin{array}{c} \begin{array}{c} \begin{array}{c} \\ \\ \\ \\ \end{array} \end{array} \begin{array}{c} \\ \\ \\ \end{array} \end{array} \begin{array}{c} \\ \\ \\ \end{array} \begin{array}{c} \\ \\ \\ \end{array} \end{array} \begin{array}{c} \\ \\ \\ \end{array} \begin{array}{c} \\ \\ \\ \end{array} \begin{array}{c} \\ \\ \\ \end{array} \end{array} \begin{array}{c} \\ \\ \\ \\ \end{array} \begin{array}{c} \\ \\ \\ \end{array} \begin{array}{c} \\ \\ \\ \\ \end{array} \begin{array}{c} \\ \\ \\ \end{array} \begin{array}{c} \\ \\ \\ \\ \\ \end{array} \begin{array}{c} \\ \\ \\ \\ \end{array} \begin{array}{c} \\ \\ \\ \\ \\ \end{array} \begin{array}{c} \\ \\ \\ \\ \end{array} \begin{array}{c} \\ \\ \\ \\ \\ \\ \\ \end{array} \begin{array}{c} \\ \\ \\ \\ \\ \\ \\ \end{array} \begin{array}{c} \\ \\ \\ \\ \\ \\ \\ \end{array} \begin{array}{c} \\ \\ \\ \\ \\ \\ \\ \end{array} \begin{array}{c} \\ \\ \\ \\ \\ \\ \\ \\ \end{array} \begin{array}{c} \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \end{array} \begin{array}{c} \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\$
SECTION 30 SECTION 30 16d duplex nail up 1.0 foot on W. side of 12 inch Burr Oak
RL314077
is marked
16d nail (1986) up 1.5 foot in N. side of 9 inch Burr Oak
18.78 feet
48.78 E
'eet '
d #4
County Road #4
terline of the way
Centerline of wild wild wild
NIO E
SECTION 31
154 duplan asil
16d duplex nail up 1.5 foot in E. side NOTE: 16d nail(1986) up 0.1 foot in E. side
All bearings are true of 10 inch Oak snag Wooded
Statement of evidence relative to this corner location is on the back of this page.
I hereby certify that this survey, plan or report was prepared by me or under my
direct supervision and that I am a duly Licensed Land Surveyor under the laws of the State of Minnesota.
of the State of Minnesota.
Terry L. Freeman, Cass County Surveyor
12/b//5 AN License No. 21367



Page 2 of 2

A000618128

Index No. V.0-03.0

Statement of Evidence

North Quarter corner Section 31, Township 143 North, Range 26 West, 5th Principal Meridian.

June K.L. Whitehorn, LS 14677, United States Department of Agriculture Forest Service(USFS), filed a Certificate of Location of Government Corner, in the Cass County Recorders Office as Document #289680.

Dec. W.C. Osufsen, LS 17767, Under contract with the United States Department of Agriculture Forest Service(USFS), filed a Certificate of Survey, in the Cass County Recorders Office as Document #325563, this survey indicates the established corner and 1986 witnesses.

May B. Hippen, technician, records of the CCHD/SO, prior to reconstruction on CSAH #4, found the USFS Brass Capped monument, down 0.1 foot, 35 feet north of centerline CSAH #4 and 1986 witnesses.

May M.E. Stefan, LS 12261, Certificate of Survey, copy on file in the CCHD/SO, Indicates Forest Service Brass Cap at the subject corner.

Aug. J.P. Major, LS 44902, Certificate of Survey for Jensen, copy on file in the CCHD/SO, Indicates found USFS Brass Capped monument at the subject corner.

Aug. B. Hippen, technician, records of the CCHD/SO, prior to reconstruction on CSAH #65, found USFS Brass Capped monument, down 0.1 foot, 58 feet, more or less, north of centerline CSAH #4 and witnessed as follows:

 9" Burr Oak(1986)
 N 50° W
 48.78 feet
 10" Oak snag(1986)
 S 38° E
 126.13 feet

 12" Burr Oak
 N 36° E
 51.30 feet
 Power Pole
 S 2° E
 106.37 feet

The monument, recovered and established references for the position are shown on the face of this document.

Analysis of the recovered record data, field evidence and survey measurements, indicates that the monument set in 1986 by the USFS, is the accepted location of this corner.

County Coordinates (Cass County North) Northing 232762.66

Easting 549256.25