

A000618349

OFFICE OF THE COUNTY RECORDER CASS COUNTY, MINNESOTA CERTIFIED, FILED, AND/OR RECORDED ON

12/24/2015 10:45:20 AM

AS DOC #: A000618349

PAGES: 2 REC FEES: 0.00

KATHRYN M. NORBY CASS COUNTY RECORDER

BY MW Dep TX#: 128046

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Licensed Land Surveyor under the laws of the State of Minnesota. 41002 22-2015 License No: PLS# 41002 18 _, Township 134N, Range 31W, Quarter Corner of Section ☐ left monument as found, ☐ lowered monument, removed monument (explain) 12-14-2015 placed a x 18" iron pipe with plastic cap stamped 囡 " RLS 41002 SKETCH OF REFERENCE TIES Corner Index: Not to Scale 1.0-5.0 NE COR SEC. 18 SET DH NAIL E. FACE TWIN 10" DAKS NBOW 7.67 WEST FACE 84 MAPLE W. FACE IOMOAK SEC . 18

Statement of evidence for this corner position is on the back of this page



Page 2 of 2 A000618349

L.0-5.0

Statement of Evidence

East Quarter corner, Section 18, Township 134 North, Range 31 West, 5th Principal Meridian, Cass County, Minnesota

1869 – T.B. Walker, US Deputy Surveyor established this corner. A wood post was set from which the following witnesses were established:

4" Elm N 29° W 18 links 6" Oak S 85° E 21 links

Information on file in the MN Historical Society, St. Paul, MN. Copies on file in the Cass County Highway Department/Surveyors Office.

1902 – Township road order shows no survey. Information on file in the Cass County Highway Department/Surveyors Office.

2015 – Patrick Trottier, PLS 41002, found no evidence of corner. Considered corner lost and established position by single proportion method between found and accepted NE and SE corners of said Section 18. Set $\frac{1}{2}$ " x 18" iron pipe with plastic cap stamped "RLS 41002" and established witnesses as shown on the face of this survey.

County Coordinates (Cass County North)

Northing 196279.04 Easting 460445.08