



A000618364

OFFICE OF THE COUNTY RECORDER CASS COUNTY, MINNESOTA CERTIFIED, FILED, AND/OR RECORDED ON

12/24/2015 10:45:35 AM AS DOC #: A000618364 PAGES: 2 REC FEES: 0.00

KATHRYN M. NORBY CASS COUNTY RECORDER BY MW Dep TX#: 128046

R.0 - 03.0139 25 Twp Rae Index No.

CERTIFICATE OF LOG	CATION OF GOVERNMENT CORNER
North Quarter corner of Section	30 ,Township <u>139 N.</u> ,Range <u>25 W.</u> , <u>5th</u> P.M.
State of Minnesota, County of	
At the corner location shown on	
On 22 May 2015 found a 4 inch square concrete post, up 0.8 foot, marked	
	outh side and S 1/4 on north side.  □ lowered monument □ removed monument (explain)
praceu	
WW SKE	TCH OF REFERENCE TIES  NOT TO SCALE
A San duplay and	NOT TO SCALE
16d duplex nail up 1.0 foot in E side of 16 inch Red Pine	Logged
di 16 ilich Red Fille	- 33
\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	
\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	\rac{1}{70} 16d duplex nail
1	up 1.0 foot in N. side of 4 inch Balsam
CECTION 10	4/g.
SECTION 19	
	, E MM.
	$\frac{N}{31}$ feet
·	\
	<i>š</i> */
SECTION 30	\$\frac{1}{2}\frac{1}{2}
SECTION 30	8/v
	M/L
16d duplex nail up 1.0 foot in W sic	de
of 10 inch Balsam	
	Wooded
NOTE:	
All bearings are true	
Statement of evidence relative to	this corner location is on the back of this page.
I hereby certify that this survey, plan or report was prepared by me or under my	
direct supervision and that I of the State of Minnesota.	am a duly Licensed Land Surveyor under the laws
of the State of Minnesota.	lan Du
	Terry L. Freeman, Cass County Surveyor
	Date 12/23/15 MN License No. 21367

## Index No. R.0-03.0

Page 2 of 2

A000618364

## Statement of Evidence

## North Quarter corner Section 30, Township 139 North, Range 25 West, 5th Principal Meridian.

Nov. Johnson and Thornton, GLO Deputy Surveyors, in the notes of the subdivision of Township 139 North,

1863 Range 25 West, set a post for the original corner and referenced it as follows:

7" Y. Pine N 2° W 49 links (32.34 feet) 10" Y. Pine S 2° W 56 links (36.96 feet) The above record is on file with the Minnesota Historical Society in St. Paul, Minnesota, copies are filed with the

Cass County Highway Department, Surveyor's Office (CCHD/SO).

May J.P Larsen, LS 143, Plat of TINGDALE BROS' ROOSEVELT TRAILS, on file in the Cass County Recorders

Office, as Document Number 87084, indicates a position for the subject corner, which is not in the plat and does

not indicate a monument.

1937 Civilian Conservation Corps (CCC), Washburn Lake Camp, Book 2, page 29, on file in the Department of Natural

Resources Office (DNR), states Fnd 4" cement Post S 1/4 19, N 1/4 30- w/B.T:

N. Pine stump N 3° E 7 fee

Feb. J.R. Worcester, Cass County Highway Department (CCHD), S.A.P. 11-658-02, on file in the CCHD, plan

indicates a Concrete Monument at corner, 1177.4 feet north of centerline at Station 114+35.

Circa W. Buckler, LS 9672, Field notes for Section 30, copy on file in the CCHD/SO, indicates a concrete monument

1986 found at the subject corner.

May B. Hippen, technician, records of the CCHD/SO, found 4 inch square concrete post, with metal bar cast in side,

2015 up 0.8 foot, marked N  $\frac{1}{4}$  S on the south side and S  $\frac{1}{4}$  S on the north side, near the crest of a ridge and marked the

following witnesses:

16" N. Pine N 33° W

29.86 feet

4" Balsam N 64° E

15.31 feet

10" Balsam

S 23° W 6.63 feet

The monument, recovered and established references for the position are shown on the face of this document.

Analysis of the recovered record data, field evidence and survey measurements, indicates that the monument recovered in 2015 by the CCHD/SO, is the accepted location of this corner.

County Coordinates (Cass County North)

Northing 110609.93 Easting 581350.79