



J.0 – 19.0

The North Quarter corner of Section 14, Township 137 North, Range 31 West of the Fifth Principal Meridian, Cass County, Minnesota, was established as part of the Original Public Land Survey during August of 1870. The Original Public Land Survey was done by Richard Cronk, U.S. Deputy Surveyor. The Original monumentation was a set wood post to mark this corner position with bearing tree as follows:

- 8" Tamarack S 02°E – 55 links (36.3 feet)
- 9" Tamarack N10°E – 38 links (25.08 feet)
- 20" Tamarack N61°W- 136.36 Links (92.00 feet)

Information on file in the MN Historical Society, St. Paul, MN. Copies in file in the Cass County Highway Dept. Surveyors Office (CCHD/SO).

On September 13, 1920, Mose Morris and Bert Anderson, Cass County Surveyors, re-surveyed the Bungo Township Road. Traveling west on 8° 30' from the Northeast corner of Section 14 to a distance of 2640.0, they set a wood hub and continued West to the Northwest corner, Survey Record 489 in Cass Book "C", Page 567.

Information on file in CCHD/SO.

On January 21, 2004, Kramer and Leas Land Surveyor Jarrett Leas set an iron monument embossed with cap number "RLS 42619". The Certificate of Survey was submitted to Cass County and received on October 29, 2004.

On November 23, 2015 a Survey Mapping Solutions, Inc. (SMS) survey crew, found no evidence of the corner.

On November 24, 2015 a Survey Mapping Solutions, Inc. (SMS) survey crew, found no evidence of the corner. Set a ½" x 24" rebar with a cap stamped "RLS 45334" based off a calculated position from the KLD Certificate of Survey dated January 21, 2004. Located 6.5 +/- feet north of the existing ditch centerline and 20 +/- feet north of the centerline of 32nd Street SW.

The recovered and established references for the position are shown on the face of this document. Analysis of the recovered record data, field evidence and survey measurements, indicates that the monument set by SMS in 2015 is the correct perpetuation of this corner.

Contacts pertaining to this corner are as follows:

- Cass County Recorder's Office
- Cass County Surveyor's Office
- Cass County Engineer's Office
- Westwood Professional Services
- KLD Land Surveying
- Bogart, Pederson & Associates Inc.
- MN DNR, Division of Lands and Minerals, Survey Section
- MN DOT District Surveys Office in Baxter

Section Corner observed by GPS

Datum: Cass County South Coordinates
Geodetic Position NAD 83 (1996 HARN Adj.)

N = 294321.131
E = 474841.875