

A000623752

OFFICE OF THE COUNTY RECORDER CASS COUNTY, MINNESOTA CERTIFIED, FILED, AND/OR RECORDED ON

8/11/2016 11:01:14 AM AS DOC #: A000623752 PAGES: 2 REC FEES: 0.00

KATHRYN M. NORBY CASS COUNTY RECORDER BY SR __Dep TX#: 132575

Two 139 Rgs 28 Index No E.0-15.0

Twp Rge midex No
CERTIFICATE OF LOCATION OF GOVERNMENT CORNER
North Quarter corner of Section 10 ,Township 139 N. ,Range 28 W. , 5th P.M.
State of Minnesota, County of Cass
At the corner location shown on the sketch:
On 18 Feb. 2004 found a 2 inch outside diameter iron pipe, up 2.5 feet.
onpiacea
SKETCH OF REFERENCE TIES
NOT TO SCALE

SECTION 3
16d duplex nail Wooded
16d duplex nail Wooded up 1.0 feet in N side of 12 inch Burr Oak
N 55 E 16d duplex nail up 1.0 feet in S side
8.35 N >7 feet 16d duplex nail up 1.0 feet in S side of 6 inch Maple
7
Clear / Cut
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
88 88
\vec{l}
SECTION 10
16d dupley noil
NOTE: 16d duplex nail up 1.0 feet in W side of 14 inch Burr Oak
All bearings are true
Statement of evidence relative to this corner location is on the back of this page.
I hereby certify that this survey, plan or
report was prepared by me or under my
direct supervision and that I am a duly
Licensed Land Surveyor under the laws of the State of Minnesota.
May TO
Terry L. Freeman, Cass County Surveyor
Date 8/10/16 MN License No. 21367

Page 1 of 2 A000623752



Index No. E.0-15.0

Statement of Evidence

North Quarter corner of Section 10, Township 139 North, Range 28 West, 5th Principal Meridian.

Johnson and Thornton, General Land Office Deputy Surveyors, notes for the subdivision of Township 139 North, April

1864 Range 28 West, set a post for the original corner and referenced it as follows:

6" Spruce N 22° W 27 links (17.82 feet) 6" Aspen S 65° E 19 links (12.54 feet) The above record is on file with the Minnesota Historical Society in St. Paul, Minnesota, copies are filed with the Cass County Highway Department, Surveyor's Office (CCHD/SO).

B. Clark, LS 231, Survey Record No. 434, Book C, page 321, on file in the CCHD/SO, states they ran east from Sept.

the established Northwest corner of Section 10. "Then set 1/4 S. cor. East 32.3 ft and turn right angle and set North 1919

93.31/2 ft. Set an iron pipe 4 ft. long 2 1/2 in. in diam." and made following witness trees:

10" Balsam S 11° W N 17° E 20.7 feet 5" Poplar 19.5 feet

B. Clark, LS 231, County Resurvey, on file in the Cass County Recorders Office, as Document Number 69799, Dec.

1921 indicates Iron Monument.

1938 Civilian Conservation Corps personnel records, Washburn Lake Book 12, page 5 on file in the Minnesota Department of Natural Resources, Outing office, state at 2640' from west set approx 1/4 cor 4" spruce.

B. Hippen, technician and J. Lamon, Forester Cass County Land Department, records of the CCHD/SO Feb. 2004 found a 2 inch outside diameter iron pipe, up 2.5 feet, on the north side of a clear cut logging area and witnessed

as follows: N 55° F

14" Burr Oak S 8° W 6" Maple 31.62 feet 36.77 feet

12" Burr Oak N 71° W 8.35 feet

B. Hippen, technician and K. Dahlman, Forester Cass County Land Department, records of the CCHD/SO Jan. found a 2 inch outside diameter iron pipe, up 2.0 feet, on the north side of a clear cut logging area and 2004 2016

witnesses in good condition.

The monument, recovered and established references for the position are shown on the face of this document.

Analysis of the recovered record data, field evidence and survey measurements, indicates that the monument recovered by CCHD/SO in 2004 is the accepted location of this corner.

County Coordinates (Cass County North) Northing 126737.09 Easting 503006.12

Easting