



A000643889

OFFICE OF THE COUNTY RECORDER
CASS COUNTY, MINNESOTA
CERTIFIED, FILED, AND/OR
RECORDED ON

9/6/2018 10:49:31 AM

AS DOC #: A000643889

PAGES: 2

REC FEES: 0.00

KATHRYN M. NORBY
CASS COUNTY RECORDER

BY NG Dep TX#: 148823

Page 1 of 2
A000643889

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Licensed Land Surveyor under the laws of the State of Minnesota.

Patrick A. Trottier

PATRICK A. TROTTIER

Date: 8-30-2018 License No: 41002
41002

OFFICE OF THE COUNTY RECORDER
County of CASS

I hereby certify that this document was filed in the Office of the County Recorder at _____ o'clock _____ M. on the _____ day of _____, 20____ A.D.

County Recorder _____

By: _____, Deputy
DOCUMENT NO. _____

NORTH QUARTER Corner of Section 33, Township 139, Range 26, 5th P.M.

On 5/3/2018 found a 2" IRON PIPE UP 1.2 FEET


left monument as found, lowered monument, removed monument (explain)

On _____ placed a _____

SKETCH OF REFERENCE TIES

Corner Index: V.0-11.0

Not to Scale



28

33

Statement of evidence for this corner position is on the back of this page



V.0-11.0

Statement of Evidence

**North Quarter corner, Section 33, Township 139 North, Range 26
West, 5th Principal Meridian, Cass County, Minnesota**

1863 – Johnson and Thornton, US Deputy Surveyors originally established this corner position while surveying the interior subdivision lines of Township 139 North, Range 26 West. A wood post was set to mark the corner position with the following witnesses:

18” Y. Pine S 65° E 54 links

11” Y. Pine N 66° W 82 links

Information on file in the MN Historical Society, St. Paul, MN. Copies on file in the Cass County Highway Department/Surveyors Office (CCHD/SO).

1916 – John Curo, County Book B, P187-190, found nothing, set a 4x4x48” oak post proportionally, returned and set a 2x48” iron boiler tube with the following witnesses:

7” R. Oak S 8° W 45.2 feet

4” R. Oak N 57°30’ W 53 feet

Copies on file in the (CCHD/SO).

1936 – CCC, Washburn Lake Book 3, P32, at 80 chains from North, found iron pipe.

Copies on file in the Washburn Lake Forestry Station.

2018 –A Stonemark survey crew found a 2 inch iron pipe up 1.2 feet from the ground, and is witnessed with the ties shown on the front of this certificate. Patrick Trottier PLS #41002, after analysis of record and survey information accepts this monument as the correct perpetuation of the corner.

County Coordinates (Cass County North NAD83/96)

Northing 105320.410

Easting 559971.290