

L.O-25.0

EAST QUARTER CORNER OF SECTION 13 TOWNSHIP 138 NORTH,
RANGE 32 WEST OF THE 5TH PRINCIPAL MERIDIAN

In 1860, the original Government Surveyor (Myer) set a post in place to mark the location of this Public Land Survey Corner with the following bearing trees:

12" Spruce, South 50 degrees West, 25 links

10" Birch, North 50 degrees East, 35 links

Information on file at the MN Historical Society, St. Paul, MN and copies at Cass County Highway Department/Surveyors Office (CCHD/SO).

In 1917, County Surveyor, Elmer Horst was conducting survey work along the East line of Section 13. In his notes he states that he set an iron monument at the position of this corner with the following new ties. (Cass County Surveyor's Master Index)

12" White Pine, North 47 degrees 30 minutes West, 74.8 feet

10" Jack Pine Stump, South 87 degrees 30 minutes East, 20.1 feet

Information on file at the CCHD/SO (County Surveyor Record Book "C", pg. 63 and Curo Book 76, pg. 48).

In 2005, a Cass County Survey crew found a 1 and 1/8" iron monument down 0.3' and 1.0' East of centerline of County Road No. 112. They created the following ties:

12" Bur Oak, North 65 degrees West, 64.94 feet

Power Pole, North 31 degrees East, 102.04 feet

Twin Maple, South 62 degrees West, 59.70 feet

Information on file at the CCHD/SO.

In 2020, Northwestern Surveying and Engineering, Inc., a private Land Surveying and Engineering firm, was conducting cadastral surveying in this area. After research and review of historic documents and records a survey crew searched for evidence of this position.

On 8/18/2020 a crew found a 1 and 1/8" iron pipe and accepted the position of this corner. One tie was found and two new ties were made as shown on the previous page.