

A000683299

OFFICE OF THE COUNTY RECORDER CASS COUNTY, MINNESOTA CERTIFIED, FILED, AND/OR RECORDED ON

4/12/2022 12:16:47 PM

AS DOC #: A000683299 PAGES: 2 REC FEES: 0.00

KATHRYN M. NORBY CASS COUNTY RECORDER

BY\_KF\_\_\_Dep TX#: 180547

				Index No.	R-19
CERTIFICA	TE OF	LOCATION	OF	GOVERNM	ENT CORNER
NORTH QUA	RTER	_ Corner of Section .	26	,Township <u>14</u>	5N,Range27W
5th Principal Meridian, State of Minnesota, County ofCASS					
At the corner location shown on the sketch:					
On 3/15/2021 found a NO ORIGINAL EVIDENCE					
☐ left monument as found, ☐ lowered monument, ☐ removed monument (explain)					
On 1/11/2022 Placed a 3/4" REBAR WELDED TO A 5.5' STEEL POST WITH CAP					
STAMPED "MN DNR LS 48249", UP 1.5', IN BLACK SPRUCE SWAMP.					
-AZIMUTHS OBSERVED WITH COMPASS -DRAWING IS NOT TO SCALE  6" BLACK SPRUCE DNR NAIL & DISC					
<b>- V-</b> 		NE SIDE, UP 1.5'	:		
		`\ \ \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\		W0.0055	
WOODED SWAMP		571	_REBAR	WOODED SWAMP	) :
		. <u>)</u>	<u>:</u>		
		22.39	*O.	اله	lv
		<b>&amp;</b>		4" BLACK SPRUCE DNR NAIL & DISC	
OACC MODIFICOUNITY	DNF	BLACK SPRUCE R NAIL & DISC SIDE, UP 1.5'		NE SIDE, UP 1.5'	
CASS NORTHCOUNTY COORDINATE SYSTEM NAD 1983 1996 ADJ.			<u>'</u>		
N = 301033.792 E = 538181.612					
Statement of evidence for this corner location is on back of this page.  AMD 2/2/2022 GNA00002.00.00.01					
I hereby certify that this plan, specification, or report was prepared by me or under my direct supervision and that I am a duly Licensed Land Surveyor under the laws of the State of Minnesota.					
SIGNATURE DANIEL A. DRUSCH  DATE 3-31-2022 License Number 48249					
Title: 📕 Land S	_	☐ Professional Engin	eer [	County Surveyor	☐ County Engineer

Page 2 of 2 A000683299

## North Quarter Corner Section 26, Township 145 North, Range 27 West, 5th P.M.

The DNR Land Survey Unit contacted the following offices for survey information on this corner:

Bureau of Land Management (BLM)
MN Secretary of State
Cass County Recorder, Auditor, Surveyor, and Highway Engineer
U.S. Forest Service
Itasca County Surveyor

- 1873 The U.S. General Land Office (GLO) survey notes and plat, on file in the MN Secretary of State's Office, describe this corner as a post set, from which:

  8" Jack Pine Stub, S 33° W, 19 links
- March, the DNR Land Survey Unit conducted a search for the corner but did not find any original evidence. As a result, this corner position was computed by Single Proportionate Measurement between the Northwest and Northeast corners of section 26. This computed position was found to measure:

2548.194 feet (GLO = 2645.28 ft) from adjoining corners.

Analysis of the available information led me to accept the computed position as the corner. Lack of government perpetuation bears out the need for the lost position.