OFFICE OF THE COUNTY RECORDER CASS COUNTY, MINNESOTA CERTIFIED, FILED, AND/OR RECORDED ON

10/23/2024 8:46:46 AM

AS DOC #: A000706833 PAGES: 2

REC FEES: 0.00

by BA Dep TX#: 199916

I hereby certify that this survey, plan, or report was was prepared by me or under my direct supervision and that I am a duly Licensed Land Surveyor under the laws of the state of Minnesota.

Daniel J. McAnin MN LIC.# 25684

## CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

NORTHEAST Corner of Section <u>30</u> , Township <u>141 N</u> , Range <u>R25 W</u> , P.M. 5th			
County of Cass, State of Minnesota			
At the corner location shown on the sketch:			
☐ On found			
☐ left monument as found ☐ lowered	monument		
⊠ On <u>July 10, 2024</u> set <u>1/2" diameter</u>	iron pipe with 1 1/2" Aluminum cap		
SKETCH OF REFERENCE TIES			
(NOT TO SCALE)			
SET DBL/DISK W FACE  S POWER POLE TAG			
S POWER POLE TAG	5 11		
DBL NAIL & DISK S19-T141N-R25W	S20-T141N-R25W		
6 IN ASH			
	<del>•</del> +		
S30-T141N-R25W	S29-T141N-R25W		
	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\		
٠	WY CONTROL		
"000°s	T141 R25 P25 P25 P25 P25 P25 P25 P25 P25 P25 P		
n <sub>o</sub>	19 20		
	DBL NAIL & DISK 30 29		
	NE FACE 8IN OAK TAG		
Cass County Coordinates	2569		
(North Zone, 2011 Adj.) N: 173880.753			
E: 583732.415	Monument Detail		

## **STATEMENT OF EVIDENCE:**

NORTHEAST CORNER OF SECTION 30 TOWNSHIP 141 NORTH, RANGE 25 WEST, (former LIMA TWP.), CASS COUNTY MINNESOTA

During the original survey of Township 141 North, Range 25 West, a wood post was set, by a GLO crew under William P. Allen and Edgar P. Putnam, to mark the corner. The bearing ties were set. Copies on file in the Cass County Highway Department/Surveyors office. (CCHD/SO).

8" Tamarac	S456dW	8 links (5.3')
8" Tamarac	S24dE	16 links (10.6')
6" Tamarac	N3dE	13 links (8.6')
8" Fir	S20dW	28 links (18.5')

- 1920 Ben F. Clark found a bearing tree stump and a 4 foot long post at this corner while measuring in a southward direction.

  (Curo Book 162, Page 20)
- A Cass County Survey crew set a monument at a pro-rated North South position determined between the East quarter corner of Section 19 and the Northeast corner of Section 31, both of which were determined by ditch and road improvements. The corner was set at the centerline of The gravel road running North and South. This was deemed to be the most supportable and equitable location.

CASS COUNTY COORDINATES (NAD 83 2011 ADJUSTMENT) N-173880.753 E-583732.415

General Land Office Information on file in the MN historical Society, St. Paul MN. Copies on file in the Cass County Highway Department/Surveyors Office (CCHD/SO).

For additional information contact:

Cass County Highway Department

County Surveyor's Office

8045 County Road 12

Walker, MN 56484

218-547-1211