


Index No. C 5

CASS COUNTY LAND CORNER RECORD

T. 133 R. 31 M. 5TH Coordinates: X _____ Y _____
E 1/4 6 Corner common to sections 5 AND 6



EXISTING SURVEYS

Original Government Survey

Year surveyed 1863
Original monument Post

Original Evidence Found

Year of search _____ By _____
Monument found _____

Bearing Trees

Species Aspen Aspen
Diameter 12" 11"
Bearing S 72 W S 84 E
Distance 38 LKS. 28 LKS.

Original Bearing Trees Found

Species _____
Diameter _____
Bearing _____
Distance _____

Subsequent Corner Restoration

Year surveyed 1/37 By Comstock & Davis
Location filed _____
Monument Computed proportioned lost position.

Evidence of Subsequent Corner Restoration

Year of search 1985 10/30 By Freedman
Find possible top of stone
11/7/85 Backhoe operator Glen Williams dug hole
14' N-S X 8' E-W 2.5' deep. Found nothing.
3" top of road, 9" fill, 1.5' sandy clay material
soil. Previous possible stone is nothing

Bearing Trees, Reference Objects

Species _____
Diameter _____
Bearing _____
Distance _____

Bearing Trees, Reference Objects

C-5

Subsequent Corner Restoration

Year surveyed 5/97 By Cent. MN Surveying
Location filed _____
Monument Set 1/2" pipe capped #17253.

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

3/03 - B. Grinna found 1/2" pipe on
9, and witnessed as follows:
Cor. Post N 45° W 39.70'
34" Cotton Wood N 45° E 62.12'
20" Turn Oak S 25° E 78.90'
A Cot L was filed.

Remonumentation certificate prepared 467573

Filed at CCRO

By #17253

Date 6/2/03