


T. 133 R. 31 M. 5TH Coordinates: X _____ Y _____
N 147 Corner common to sections 6 AND 7



○ = Corner

EXISTING SURVEYS

Original Government Survey
 Year surveyed 1863
 Original monument Post

Original Evidence Found
 Year of search _____ By _____
 Monument found _____

Bearing Trees
 Species PINE PINE _____
 Diameter 5" 6" _____
 Bearing S89E N86E _____
 Distance 314 LKS. 319 LKS. _____

Original Bearing Trees Found
 Species _____
 Diameter _____
 Bearing _____
 Distance _____

Subsequent Corner Restoration
 Year surveyed 1915 By N. D. Gorman
 Location filed County Book 'B' P. 480-495
 Monument SET CORNER PROPORTIONALLY.

Evidence of Subsequent Corner Restoration
 Year of search 1985 10/29 By Freeman
and cast iron monument; 1977 trees

Bearing Trees, Reference Objects
 Species _____
 Diameter _____
 Bearing _____
 Distance _____

Bearing Trees, Reference Objects

Subsequent Corner Restoration
 Year surveyed _____ By _____
 Location filed _____
 Monument _____

Evidence of Subsequent Corner Restoration Found
 Year of search _____ By _____
CERTIFICATE - AL WELLE - MINN DOT 1977
Doc # 251314
2-15-77 Found 2" capped pipe (up 1.5') leaning
North 15° a distance of 76.15' west of corner
location.
2-22-77 Placed Minn Hwy Dept cast iron
monument 76.15' East of found pipe. Ties:
12" Elm NW 51.30'; top center of old bridge
piling NE 81.40'; 10" Twin Oak SE 143.58'; 12"
White Oak SW 99.40'. Monument is located
on old fence line and 8' north of E of old
road.