


Index No. J 15

CASS COUNTY LAND CORNER RECORD

T. 133 R. 31 M. 5TH Coordinates: X _____ Y _____
N 1/4 15 Corner common to sections 10 and 15



○ = Corner

EXISTING SURVEYS

Original Government Survey
Year surveyed 1863
Original monument Post

Original Evidence Found
Year of search _____ By _____
Monument found _____

Bearing Trees
Species SPRUC W. BIRCH
Diameter 4" 7"
Bearing N18E S14E
Distance 16 LKS 26 LKS

Original Bearing Trees Found
Species _____
Diameter _____
Bearing _____
Distance _____

Subsequent Corner Restoration
Year surveyed 1910 By John Luo
Location filed COUNTY RECORD BOOK "A" P. 28, 29
Monument FIND NORTH OLD GOVT B.T.S SET 8x8x36"
STONE IN CONCRETE.
1915- E.B. HOEST COUNTY BOOK "C" P. 83 FIND CONCRETE MONUMENT

Evidence of Subsequent Corner Restoration
Year of search _____ By _____
1910 - also on microf. film - roll 115 BK 91 P. 35

Bearing Trees, Reference Objects
Species _____
Diameter _____
Bearing _____
Distance _____

Bearing Trees, Reference Objects
Species _____
Diameter _____
Bearing _____
Distance _____

J-15
Subsequent Corner Restoration
Year surveyed _____ By MW Dot
Location filed _____
Monument Plan indicates iron pin,
2.1" N. of P.O.T. 232+913 and
witnesses:
5" Elm NW 54.4'
6" Ash NNE 44.2'
4" Ash NE 48.5'

Evidence of Subsequent Corner Restoration Found
Year of search Sept 1902 By _____
Truprd order shows no survey
May 1902, Truprd order shows no survey

Remonumentation certificate prepared _____
Filed at _____

By _____
Date _____