Index No. J 21

CASS COUNTY LAND CORNER RECORD

T. 133 R. 31 M. 5TH Coordinates: X _____ Y _____

NE 14 Corner common to sections 11, 12, 13, 14



O = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1863

Original monument LOST

Original Evidence Found

Year of search _____ By _____

Monument found _____

Bearing Trees

Species	W. OAK	SPRUCE	BIRCH	W. OAK
Diameter	15"	10"	10"	18"
Bearing	N 43½ E	S 50¾ W	N 57¼ W	S 69¾ W
Distance	22 LKS.	28 LKS.	25 LKS.	46 LKS.

Original Bearing Trees Found

Species				
Diameter				
Bearing				
Distance				

Subsequent Corner Restoration

Year surveyed 1912 By JOHN CURO

Location filed COUNTY SURVEY RECORD BOOK "A" P496-498

Monument SET HUB: 7 ACR FROM OLD GUNT B.T.S

SET 2½ x 36" GALV I.P IN CONCRETE

Evidence of Subsequent Corner Restoration

Year of search 1985 10/24 By Freeman

Found I.P. capped down 0.5' and 1953 State Hwy. Dept. ties

June 1912, Twp order shows no survey

Bearing Trees, Reference Objects

Species	OAK	OAK STUMP	F.P.	OAK STUB
Diameter	10"	8"	3"	
Bearing	N 50-45 E	N 69-02 E	S 0-33 W	N 76-15 W
Distance	12.85'	25.80'	27.10'	70.70'

Bearing Trees, Reference Objects

J-21

Subsequent Corner Restoration

Year surveyed _____ By _____

Location filed _____

Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

CERTIFICATE - L. C. MAY - MINN DOT - 1953

Doc # 258160H

Found an iron pipe. Placed a galvanized iron monument with aluminum. Ties: Iron monument 100' NE; Iron monument 100' NE.

Remonumentation certificate prepared _____ By _____

Filed at _____ Date _____