Index No. J 25

CASS COUNTY LAND CORNER RECORD

T. 133 R. 31 M. 5TH Coordinates: X _____ Y _____

NE 13 Corner common to sections 12 & 13 AND 7 & 18 - 133 - 30



EXISTING SURVEYS

Original Government Survey

Year surveyed 1858

Original monument LOST

Original Evidence Found

Year of search _____ By _____

Monument found _____

Bearing Trees

Species	PINE	PINE	PINE	PINE
Diameter	8"	6"	12"	7"
Bearing	S11W	N80W	S49E	N21E
Distance	23 LKS	14 LKS	5 LKS	9 LKS

Original Bearing Trees Found

Species				
Diameter				
Bearing				
Distance				

Subsequent Corner Restoration

Year surveyed _____ By MN DOT

Location filed R/W Plan

Monument Iron pin, 32.9' North of P.O.T. 365+25.1.

Evidence of Subsequent Corner Restoration

Year of search 7/97 By Cent. MN. Surveying

Set iron pipe capped RLS #17253 at MN DOT position.

Bearing Trees, Reference Objects

Species				
Diameter				
Bearing				
Distance				

Bearing Trees, Reference Objects

J-25

Subsequent Corner Restoration

Year surveyed 3/03 By B. Grovna

Location filed

Monument Found 1/2" iron pipe, 28'± N. of Hwy #210 and 9'± W. of Approach. A C of L was filed.

P. Pole	NW,	46.21'	PK nail
8" Aspen	NNW,	85.16'	spike
Gate Post	SSW,	107.84'	Spike
Tel Ped	SW,	110.18'	Center

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

Remonumentation certificate prepared #468350 By #17253

Filed at CCRO Date 6/13/03