


Index No. L 13

CASS COUNTY LAND CORNER RECORD

T. 133 R. 31 M. 5TH Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_  
E 1/4 16 Corner common to sections 15 AND 16



EXISTING SURVEYS

**Original Government Survey**

Year surveyed 1863  
Original monument POST

**Bearing Trees**

Species	<u>ASPEN</u>	<u>ASPEN</u>
Diameter	<u>6"</u>	<u>8"</u>
Bearing	<u>N86E</u>	<u>S68W</u>
Distance	<u>192 LKS</u>	<u>82 LKS</u>

**Original Evidence Found**

Year of search \_\_\_\_\_ By \_\_\_\_\_  
Monument found \_\_\_\_\_

**Original Bearing Trees Found**

Species	_____	_____
Diameter	_____	_____
Bearing	_____	_____
Distance	_____	_____

○ = Corner

**Subsequent Corner Restoration**

Year surveyed 1915 By E. B. HOEST  
Location filed COUNTY BOOK 'C' P. 87  
Monument SET WOOD POST

**Evidence of Subsequent Corner Restoration**

Year of search 1981, 1982 By MN/DOT  
End iron set in 1915 in Road - error made in setting - corner is 108.47' East. set east iron monument.

Certificate - welle - MN/DOT - 1987 - Doc # 298406

**Bearing Trees, Reference Objects**

Species	_____	_____
Diameter	_____	_____
Bearing	_____	_____
Distance	_____	_____

**Bearing Trees, Reference Objects**

<u>I.P.</u>	<u>Poplar</u>	<u>Poplar</u>
<u>2"</u>	<u>6"</u>	<u>8"</u>
<u>West</u>	<u>SOUTH</u>	<u>SW</u>
<u>108.47'</u>	<u>7.51'</u>	<u>11.71'</u>

**Subsequent Corner Restoration**

Year surveyed 1997 By Nielsen, #11865  
Location filed CCSO  
Monument Cert. of Survey indicates monument found.

**Evidence of Subsequent Corner Restoration Found**

Year of search \_\_\_\_\_ By \_\_\_\_\_

Certificate - Al welle - 1987

May 1914, Twp rd order shows no survey

Aug 1914, Twp rd order shows no survey

Re-monumentation certificate prepared \_\_\_\_\_ By \_\_\_\_\_  
Filed at \_\_\_\_\_ Date \_\_\_\_\_