Index No. A R CASS COUNTY LAND	CORNER RECORD	
T 134 R 30 M 5TH Coordinates: X	Y	
T. 134 R. 30 M. 5TH Coordinates: X NEZ Corner common to sections 1, 2 Awa	35, 36-135-30	
FXISTING	SURVEYS	
Original Government Survey	Original Evidence Found	
Year surveyed 1858	Year of searchBy	
Original monument losr	Monument found	
Bearing Trees	Original Bearing Trees Found	O = Corner
Sparing MALM GILLED TAM. TAM	Species	
Diameter 14" 7" 8" Bearing N49", E N33 W 574 W	Diameter	
Bearing $\mu 49^{\circ}Z = N33 \omega - 574 \omega$	Bearing	
Distance 98 LKS 114 LKS 206 LKS	Distance	
Subsequent Corner Restoration	Evidence of Subsequent (Corner Restoration
Year surveyed 1911 By A. W. Mouston	Year of search 19/5 By F.	A. Donner
Location filed COUNTY SURVEY RECORD BOOK A P465-472	microfilm-voll 115 BK94 P. 14	′3
Monument Fro STAKE : 3/4" BLACK IRON APK SOT BY B.B.	Year of search 1915 By F. microfilm-voll 115 BK94 P. 14 Find halfinch iron pin up	8"- no BIT.5
2/50 00 microfilm-Roll 105 BK49 P. 144		
4130 101 101 101 101 101 101 101 101 101		
Bearing Trees, Reference Objects	Bearing Trees, Reference	B Objects
Species		
Diameter		
Bearing		
Distance		
rear surveyed 1999 By ONR J. Walker ocation filed State of MN & CCSO Monument Certificate of Survey indicates iron pipe found, Set by Landeckere	Year of search By	
Associ		
· · · · · · · · · · · · · · · · · · ·		
		
<u> </u>		
Remonumentation certificate prepared	Ву	
Filed at	Date	