


Index No. A 13

CASS COUNTY LAND CORNER RECORD

T. 134 R. 32 M. 5TH Coordinates: X NE 4 Y 3, 4 AND 33, 34-135-32
Corner common to sections



EXISTING SURVEYS

Original Government Survey
Year surveyed 1858
Original monument Post

Original Evidence Found
Year of search _____ By _____
Monument found _____

Bearing Trees
Species _____
Diameter NO TIE TREES AVAILABLE
Bearing _____
Distance _____

Original Bearing Trees Found
Species _____
Diameter _____
Bearing _____
Distance _____

Subsequent Corner Restoration
Year surveyed _____ By _____
Location filed _____
Monument _____

Evidence of Subsequent Corner Restoration
Year of search 1985, 1986 By Surveyors Office
9/19/85 - dug at proportional point - dug 10' E-W x
8' N-S x 2.5' deep. 6" top, 2" fill to layer
of corduroy - found nothing.
8/25/86 - set cast iron monument at proportional
point provided by Camstock & Davis.

Bearing Trees, Reference Objects
Species _____
Diameter _____
Bearing _____
Distance _____

Bearing Trees, Reference Objects
telespar monuments
2" x 36" w/ stamped alum. cap
S 45° W 45.0' S 45° E 40.0'
45.0' 40.0'
Certificate - Doc # 297515 - Curc - 1987

Subsequent Corner Restoration
Year surveyed _____ By _____
Location filed _____
Monument _____

Evidence of Subsequent Corner Restoration Found
Year of search _____ By _____
Certificate - Walt Curc - 1987
Doc. # 297515

Subsequent Corner Restoration
Year surveyed _____ By _____
Location filed _____
Monument _____

AUG. 2000 - CCSSO
Fnd. in place; CIM dwn 2.7' in gravel
rd. E/W. Located 1' S & 9 1/2" st. SW.
REF. TIES:
Telspar Mon. S 45° W 45.0' (exist. tie)
Telspar Mon. S 45° E 40.0' (exist. tie)
P.K. in N. End 18" CMP N 32° E 21.41'
" " S. End " " S 32° E 19.03'
- corner GPS 10/15/02 CCSSO
Spk/washer, flush, on E, 12" ± W. of cul.

Remonumentation certificate prepared _____
Filed at _____

By _____
Date _____