


Index No. T 17

CASS COUNTY LAND CORNER RECORD

T. 134 R. 32 M. 5th Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_  
E/4 RT Corner common to sections 26, 27



○ = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1870  
Original monument Post

Original Evidence Found

Year of search \_\_\_\_\_ By \_\_\_\_\_  
Monument found \_\_\_\_\_

Bearing Trees

Species	<u>Bl. Pine</u>	<u>N. Pine</u>		
Diameter	<u>8"</u>	<u>12"</u>		
Bearing	<u>N70E</u>	<u>N31W</u>		
Distance	<u>141 LKS.</u>	<u>115 LKS.</u>		

Original Bearing Trees Found

Species	_____	_____	_____	_____
Diameter	_____	_____	_____	_____
Bearing	_____	_____	_____	_____
Distance	_____	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 1941 By \_\_\_\_\_  
Location filed C. DITCH SURVEY BK 173 A  
Monument Box 3 C. DITCH SURVEY BOOKS  
PG. 16

Evidence of Subsequent Corner Restoration

Year of search 11/2/98 By LS #13334  
FOUND COUNTY MONUMENT

Bearing Trees, Reference Objects

Species	_____	_____	_____	_____
Diameter	_____	_____	_____	_____
Bearing	_____	_____	_____	_____
Distance	_____	_____	_____	_____

Bearing Trees, Reference Objects

_____	_____	_____	_____	_____
_____	_____	_____	_____	_____
_____	_____	_____	_____	_____
_____	_____	_____	_____	_____

T-17

Subsequent Corner Restoration

Year surveyed 7/2003 By CCSO  
Location filed #2001.022  
Monument Found 1" OD IP, down 0.5',  
4'± E. of E. Co. Rd. #106 and witness.

Evidence of Subsequent Corner Restoration Found

Year of search \_\_\_\_\_ By \_\_\_\_\_

<u>J. Pine 6"</u>	<u>N62°W</u>	<u>71.20'</u>	<u>*</u>
<u>P. Pole</u>	<u>S70°E</u>	<u>35.14'</u>	<u>*</u>
<u>14" J. Pine</u>	<u>S65°W</u>	<u>79.99'</u>	<u>*</u>

\*distance to double head nail

Remonumentation certificate prepared \_\_\_\_\_ By \_\_\_\_\_  
Filed at \_\_\_\_\_ Date \_\_\_\_\_