


Index No. V 17

CASS COUNTY LAND CORNER RECORD

T. 135 R. 30 M. 5TH Coordinates: X _____ Y _____
NE 34 Corner common to sections 26, 27, 34, 35



EXISTING SURVEYS

Original Government Survey

Year surveyed 1869

Original monument POST

	Bearing	Trees	
Species	<u>TAM</u>	<u>TAM</u>	<u>TAM</u>
Diameter	<u>4"</u>	<u>5"</u>	<u>4"</u>
Bearing	<u>N61E</u>	<u>S60E</u>	<u>N85W</u>
Distance	<u>18 LKS.</u>	<u>13 LKS.</u>	<u>27 LKS</u>

Original Evidence Found

Year of search _____ By _____

Monument found _____

Original Bearing Trees Found

Species	Diameter	Bearing	Distance

O = Corner

Subsequent Corner Restoration

Year surveyed 1921 By E.B. HARST

Location filed COUNTY RESURVEY E-33"

Monument IRON MONUMENT AND OLD GOUT BITS
1921, E.B. HARST, COUNTY BOOK C' P. 112 FOUND 4" TAM STUMP BIT, SET 2x10" I.M.

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance

Evidence of Subsequent Corner Restoration

Year of search 1925 By SCHULTZ

COUNTY BOOK "D" P. 167 END POLE IN ROAD AT P. 1
RDS- E-N-S, 2' N OF FENCE WEST

OCT. 1905 W.H. Hallett
TRUP RD ORDER SHOWS SURVEY

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance

V-17

Subsequent Corner Restoration

Year surveyed 6/25/03 By CCSO

Location filed _____

Monument FL 2" nail, flush, 2' ± W. of E
Co. Rd. #107 North, 4' ± N. of E East, on
E old grade South, 5' ± South of fence
to West. The fence west is steel
posts 1' ± North of old posts
still visible.

tele post N 85° W * 24.01'
P-pole S 42° E * 54.17'
12" N. Pine S 67° E * 236.40'
P-pole N 8° E * 194.76'
* - Dist's meas. to dbl rd nail

Aug. 2003 B. Grivna # 17253
cert. of Sur. Shows mon. found

Aug. 2004 B. Grivna # 17253
cert. of sur. shows mon. found

Nov. 2004 B. Grivna # 17253
cert. of survey monument found

Evidence of Subsequent Corner Restoration Found

Year of search Oct. 1903 By W.H. Hallett

TRUP RD ORDER SHOWS SURVEY

Remonumentation certificate prepared _____
Filed at _____

By _____
Date _____