


Index No. A 11

CASS COUNTY LAND CORNER RECORD

T. 135 R. 32 M. 5TH Coordinates: X Y
N 1/4 4 Corner common to sections 4 AND 33-136-32



EXISTING SURVEYS

Original Government Survey

Year surveyed 1858

Original monument POST

Species	Bearing	Trees
<u>SP. PINE</u>	<u>SP. PINE</u>	
<u>14"</u>	<u>10"</u>	
<u>SOUTH</u>	<u>S70E</u>	
<u>31 LKS.</u>	<u>10 LKS.</u>	

Original Evidence Found

Year of search _____ By _____

Monument found _____

Original Bearing Trees Found

Species	Bearing	Trees
_____	_____	_____
_____	_____	_____
_____	_____	_____
_____	_____	_____

Subsequent Corner Restoration

Year surveyed _____ By _____

Location filed _____

Monument _____

Evidence of Subsequent Corner Restoration

Year of search 1985 8/26 By Terry Freeman

looked for corner - not definite search area

1986 - set cast iron in G road and fence S.

1987 - Curo - Certificate - Doc # 297161

1985 - also dug for corner - found nothing

Bearing Trees, Reference Objects

Species	Bearing	Distance
_____	_____	_____
_____	_____	_____
_____	_____	_____
_____	_____	_____

Bearing Trees, Reference Objects

Species	Bearing	Distance
_____	_____	_____
_____	_____	_____
_____	_____	_____
_____	_____	_____

Subsequent Corner Restoration

Year surveyed _____ By _____

Location filed _____

Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

Cert. ficate - Walt Curo - 1987

Doc. # 297161

2000 - CCSO

Find in place 4" CIM down 0.9'. Located

G 72' St. and 35' ± N of fence corner.

REF. TIES:

<u>10" W. Oak</u>	<u>S 74° W</u>	<u>104.37'</u>
<u>6" Aspen</u>	<u>S 16° W</u>	<u>30.58'</u>
<u>P. Pole</u>	<u>N 76° E</u>	<u>148.83'</u>

* distances to dbl. hd nails

Re monumentation certificate prepared _____

Filed at _____

By _____

Date _____