


Index No. P 9

CASS COUNTY LAND CORNER RECORD

T. 136 R. 29 M. 5TH Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_  
E 1/4 20 Corner common to sections 20, 21



○ = Corner

EXISTING SURVEYS

**Original Government Survey**  
 Year surveyed 1870  
 Original monument POST

Species	Bearing	Trees
<u>B. Pine</u>	<u>B. Pine</u>	
Diameter <u>5"</u>	<u>6"</u>	
Bearing <u>S 7 E</u>	<u>S 12 W</u>	
Distance <u>138 LKS</u>	<u>128 LKS</u>	

**Original Evidence Found**  
 Year of search \_\_\_\_\_ By \_\_\_\_\_  
 Monument found \_\_\_\_\_

**Original Bearing Trees Found**

Species	Bearing	Distance
_____	_____	_____
Diameter _____	_____	_____
Bearing _____	_____	_____
Distance _____	_____	_____

**Subsequent Corner Restoration**  
 Year surveyed 1913 By HARRY TODD  
 Location filed COUNTY SURVEY RECORD BOOK 'B' P. 305-309  
 Monument SET 3x3x27" S. PINE STAKE PROPORTIONALLY

**Evidence of Subsequent Corner Restoration**  
 Year of search 1998 By LLSO  
incl. 3'x3" alum. capped monument #11395 RLS

**Bearing Trees, Reference Objects**

Species	Bearing	Distance
_____	_____	_____
Diameter _____	_____	_____
Bearing _____	_____	_____
Distance _____	_____	_____

**Bearing Trees, Reference Objects**

R. Oak	N. Pine	J. Pine
<u>3"</u>	<u>17"</u>	<u>11"</u>
<u>N 55° W</u>	<u>N 10° E</u>	<u>S 60° E</u>
<u>69.33'</u>	<u>191.80'</u>	<u>58.27'</u>

**Subsequent Corner Restoration**  
 Year surveyed \_\_\_\_\_ By \_\_\_\_\_  
 Location filed \_\_\_\_\_  
 Monument August 1905 W.H. Luffman  
Trap Road order shows survey  
December 1913 Harry S. Todd  
Trap Road Order shows survey

**Evidence of Subsequent Corner Restoration Found**  
 Year of search \_\_\_\_\_ By \_\_\_\_\_

Remonumentation certificate prepared \_\_\_\_\_ By \_\_\_\_\_  
 Filed at \_\_\_\_\_ Date \_\_\_\_\_