Index No. A 5

CASS COUNTY LAND CORNER RECORD

T. 136 R. 30 M. 5TH Coordinates: X _____ Y _____

NE 6 Corner common to sections 5,6



O = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1870

Original monument R.C. Post

Original Evidence Found

Year of search _____ By _____

Monument found _____

Bearing Trees

Species	W. Pine	N. Pine		
Diameter	11"	12"		
Bearing	S82¼E	S32W		
Distance	218 LKS	166 LKS.		

Original Bearing Trees Found

Species				
Diameter				
Bearing				
Distance				

Subsequent Corner Restoration

Year surveyed 1908 By John Curo

Location filed County Survey Record Book "B" P. 140-157

Monument Fnd old Govt B.T Stumps: 11" W. Pine S82-15E 218 LKS, 12" N. Pine S32W 166 LKS. Set true Corner

also on microfilm - roll 115 BK 85 P. 249

Bearing Trees, Reference Objects

Species				
Diameter				
Bearing				
Distance				

Evidence of Subsequent Corner Restoration

Year of search 1977 By R.F. Schneider for Hwy Dept

CoRD #28

Corner position from road stationing

Bearing Trees, Reference Objects

Subsequent Corner Restoration

Year surveyed JAN 1995 By MN DNR

Location filed STR FILE - CCSO

Monument ALUM CAP CO. SURV. MON. IN BITUM.

STATIC GPS OCCUPATION

PUNCH HOLE TOP W. END 15" CMP 208° 51.80'

" " " E END 15" CMP 150° 43.94

DNR RP UP 1.0 E. SIDE BRACE POST 326° 89.07

7/01 CCSO

Found alum cap telspar mon flush, on ℄ co. rd. #28, 9' E of ℄ 41st Ave.

Fence cor post S29'E 79.50' *

18" Cmp S40°W 51.68' to PK

Tele fed post N 36°W 89.08' *

Street sign E. flange N 10°W 53.71'

* Dist to dbl hd nail

-Corner GPS 9/12/02 CCSO

Alum cap

Oct. 1909 Twp Rd order shows no survey

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

Remonumentation certificate prepared _____ By _____

Filed at _____ Date _____