


Index No. E17

CASS COUNTY LAND CORNER RECORD

T. 136 R. 31 M. 5TH Coordinates: X _____ Y _____
NE 10 Corner common to sections 2, 3, 10, 11



EXISTING SURVEYS

Original Government Survey

Year surveyed 1870

Original monument POST

Species	Bearing	Trees	Distance
<u>W. BIRCH</u>	<u>W. BIRCH</u>	<u>W. BIRCH</u>	<u>APEN</u>
<u>6"</u>	<u>5"</u>	<u>5"</u>	<u>6"</u>
<u>S62W</u>	<u>N39 3/4 E</u>	<u>S79 E</u>	<u>N 83 1/2 W</u>
<u>22 LKS.</u>	<u>6 LKS</u>	<u>16 LKS</u>	<u>20 LKS</u>

Original Evidence Found

Year of search _____ By _____

Monument found _____

Original Bearing Trees Found

Species	Bearing	Distance
_____	_____	_____
_____	_____	_____
_____	_____	_____
_____	_____	_____

Subsequent Corner Restoration

Year surveyed 1911 By A. W. Moulton

Location filed COUNTY SURVEY RECORD BOOK "A" P. 456-464

Monument FOUND STONE W/ "X" SET BY JOHN USHER
SET PROBABLY 1870. SET 2x4x8" CAPED GALV
1/2" IN CONCRETE
also on microfilm - roll 105 BK 50 P. 116-117, 118

Bearing Trees, Reference Objects

Species	Bearing	Distance
_____	_____	_____
_____	_____	_____
_____	_____	_____
_____	_____	_____

Evidence of Subsequent Corner Restoration

Year of search 7/17/03 By CCSO

Set 18" telescope w/ alum cap, down 0.1, on
E, N, E, and W, 12' ± S. of connecting E.

Bearing Trees, Reference Objects

P-pole	Bearing	Distance	P-pole	Bearing	Distance
_____	_____	_____	<u>W. Oak</u>	<u>Birch</u>	_____
_____	_____	_____	<u>5"</u>	<u>9"</u>	_____
<u>N 76 W</u>	<u>N 60° E</u>	<u>S 63° W</u>	<u>S 42° E</u>	_____	_____
<u>172.82</u>	<u>75.65</u>	<u>49.39</u>	<u>43.94</u>	_____	_____

E-17

Subsequent Corner Restoration

Year surveyed 6/1905 By N.W. Hicks

Location filed Record Order @ Top file

Monument Surveyor's Report shows
stone set by Usher is 17.53 south
of a straight line.

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

Remonumentation certificate prepared A000668733
Filed at _____

By _____
Date _____