


Index No. _____

CASS COUNTY LAND CORNER RECORD

T. _____ R. _____ M. _____ Coordinates: X _____ Y _____

Corner common to sections _____



= Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed _____
Original monument _____

Original Evidence Found

Year of search _____ by _____
Monument found _____

Bearing Trees

Species _____
Diameter _____
Bearing _____
Distance _____

Original Bearing Trees Found

Species _____
Diameter _____
Bearing _____
Distance _____

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed:
Monument:

Evidence of Subsequent Corner Restoration

Year of search _____ By _____
Location filed:
Monument:

Bearing Trees, Reference Objects

Species _____
Diameter _____
Bearing _____
Distance _____

Bearing Trees, Reference Objects

Species _____
Diameter _____
Bearing _____
Distance _____


Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed:
Monument:

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____
Location filed:
Monument:

T. 137 R. 29 M. 5th Coordinates: X _____ Y _____
NE 20 Corner common to sections 16, 17, 20, 21



EXISTING SURVEYS

Original Government Survey

Year surveyed 1865

Original monument Post

Bearing Trees	
Species <u>Bl. Pine</u>	<u>Bl. Pine</u>
Diameter <u>10"</u>	<u>12"</u>
Bearing <u>N 15 E</u>	<u>N 6 1/2 W</u>
Distance <u>83 LKS.</u>	<u>94 LKS.</u>

Original Evidence Found

Year of search _____ By _____

Monument found _____

Original Bearing Trees Found

Species _____	_____
Diameter _____	_____
Bearing _____	_____
Distance _____	_____

Subsequent Corner Restoration

Year surveyed _____ By ROAD SURVEY

Location filed COUNTY BOOK "C" P. 474

Monument IRON MONUMENT
1914, F.A. DANNER, BOOK "C" P. 564 FWD. FLAT IRON ROD
SET BY CURO SET 2x48" I.M.W. CONCRETE

Evidence of Subsequent Corner Restoration

Year of search 1942 By JOHN CURO

COUNTY BOOK "D" P. 306, 2" I.P. W/ CAP TORN OFF

Bearing Trees, Reference Objects

Species	J. PINE	ASPEN	J. PINE
Diameter	<u>5"</u>	<u>4"</u>	<u>6"</u>
Bearing	<u>S 42-33 W</u>	<u>N 62-20 E</u>	<u>S 27-30 E</u>
Distance	<u>51.75'</u>	<u>57.25'</u>	<u>46.65'</u>

Bearing Trees, Reference Objects

SLED SHOE	J. PINE	J. PINE	ANGLE IRON
<u>1x3x20"</u>	<u>10"</u>	<u>12"</u>	<u>2x2x20</u>
<u>N 70-15 E</u>	<u>S 79-41 E</u>	<u>S 42-05 W</u>	<u>N 37-50 W</u>
<u>49.65'</u>	<u>89.35'</u>	<u>55.20'</u>	<u>55.50'</u>

N-9

Subsequent Corner Restoration

Year surveyed 1914 By J. Curo

Location filed Tap Rd. Order a Tap file

Monument Surveyor's Report indicates Iron.

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

CERTIFICATE - C.J. BARK - ASST HWY ENGINEER - 1922

Found 2" Iron pipe set in concrete by John Curo

TIES: 2" hollow iron pipe SW 46.7'; 2" hollow

iron pipe SE 46.7'; 2" hollow iron pipe NW

46.7'; 2" hollow iron pipe NE 46.7'.