


Index No. G 9

CASS COUNTY LAND CORNER RECORD

T. 138 R. 30 M. 5th Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_  
E148 Corner common to sections 8, 9



EXISTING SURVEYS

**Original Government Survey**

Year surveyed 1865

Original monument POST

**Bearing Trees**

Species	<u>N. PINE</u>	<u>BL. PINE</u>	_____
Diameter	<u>22"</u>	<u>12"</u>	_____
Bearing	<u>N 72 3/4 E</u>	<u>N 73 1/4 W</u>	_____
Distance	<u>306 LKS.</u>	<u>460 LKS</u>	_____

**Original Evidence Found**

Year of search \_\_\_\_\_ By \_\_\_\_\_

Monument found \_\_\_\_\_

**Original Bearing Trees Found**

Species	_____	_____	_____
Diameter	_____	_____	_____
Bearing	_____	_____	_____
Distance	_____	_____	_____

**Subsequent Corner Restoration**

Year surveyed 1924 By Minn. Hwy Dept.

Location filed RLW map in Recorder's Office - Lathrop

Monument to Pine River.

distance of 1639.4' W to & STRD 19(371)

and 2687.0' to C148 which is iron pipe.

**Evidence of Subsequent Corner Restoration**

Year of search \_\_\_\_\_ By \_\_\_\_\_

**Bearing Trees, Reference Objects**

Species	_____	_____	_____
Diameter	_____	_____	_____
Bearing	_____	_____	_____
Distance	_____	_____	_____

**Bearing Trees, Reference Objects**

Species	_____	_____	_____
Diameter	_____	_____	_____
Bearing	_____	_____	_____
Distance	_____	_____	_____

**Subsequent Corner Restoration**

Year surveyed \_\_\_\_\_ By \_\_\_\_\_

Location filed \_\_\_\_\_

Monument \_\_\_\_\_

**Evidence of Subsequent Corner Restoration Found**

Year of search \_\_\_\_\_ By \_\_\_\_\_

Re monumentation certificate prepared \_\_\_\_\_ By \_\_\_\_\_

Filed at \_\_\_\_\_ Date \_\_\_\_\_