Index No. P13

CASS COUNTY LAND CORNER RECORD

T. 138 R. 30 M. 5TH Coordinates: X _____ Y _____

E1/4 21 Corner common to sections 21, 22



O = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1865

Original monument Post

Bearing Trees

Species	Y. Pine	Y. Pine
Diameter	16"	15"
Bearing	N89W	N82E
Distance	71 LKS.	30 LKS

Original Evidence Found

Year of search _____ By _____

Monument found _____

Original Bearing Trees Found

Species			
Diameter			
Bearing			
Distance			

Subsequent Corner Restoration

Year surveyed 1915 By John Curo

Location filed County Surveyor Record Book "B" P 114

Monument Set 2"x48" Galv. I.P.

1917, E.B. Horst Book "B" P598 Fnd I.M.

1915 - N.D. Gorman - microfilm - roll 115 BK90

P.20 Fnd corner. P.49 Set I.M.

Bearing Trees, Reference Objects

Species			
Diameter			
Bearing			
Distance			

Evidence of Subsequent Corner Restoration

Year of search 1924 By Minn. Hwy Dept

R/W map in Recorder's office - Lothrop to Pine River.

Iron pipe w/cap 1125.8' W of C - distance to E1/4 22 (Iron pipe) is 2670.6'

Bearing Trees, Reference Objects

Subsequent Corner Restoration

Year surveyed 1917 By John Curo

Location filed Microfilm - Roll 105 - Curo notes - BK(?) P37

Monument iron monument

Dec 1997 B. Grivna # 17253
Cert. of Svy. shows Mon. found

Sept 2003 B. Grivna # 17253
Cert of Svy. shows Mon. found

Aug. 1904 W.H. Hallett
Twp Rd order shows survey

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

Remonumentation certificate prepared _____ By _____

Filed at _____ Date _____