


T. 138 R. 30 M. 5TH Coordinates: X _____ Y _____
NE 27 Corner common to sections 22, 23, 26, 27



○ = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1865
Original monument Post

Original Evidence Found

Year of search _____ By _____
Monument found _____

Species	Bearing Trees			
	<u>BL. PINE</u>	<u>BL. PINE</u>	<u>BL. PINE</u>	<u>BL. PINE</u>
Diameter	<u>5"</u>	<u>4"</u>	<u>5"</u>	<u>4"</u>
Bearing	<u>N31E</u>	<u>N61W</u>	<u>S64W</u>	<u>S43E</u>
Distance	<u>7 LKS.</u>	<u>17 LKS</u>	<u>15 LKS</u>	<u>3 LKS</u>

Original Bearing Trees Found

Species	_____	_____	_____
Diameter	_____	_____	_____
Bearing	_____	_____	_____
Distance	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 1913 By John Corp
 Location filed COUNTY SURVEY RECORD BOOK B, P289-300
 Monument FIND OLD GUY B.T STUMPS: 5" BL. PINE
N31E 7 LKS, 5" BL. PINE S64W 15 LKS, SET 2 1/2 x 40"
GALV I.P. W/CAP IN CONCRETE

Evidence of Subsequent Corner Restoration

Year of search 1924 By Minn. Hwy Dept.
R/W map in Recorder's Office - lot trap to line by
iron pipe w/cap 1105.5' E of road

Bearing Trees, Reference Objects

Species _____
 Diameter _____
 Bearing _____
 Distance _____

Bearing Trees, Reference Objects

Species _____
 Diameter _____
 Bearing _____
 Distance _____

R-17

Subsequent Corner Restoration

Year surveyed 5/2000 By CCSO
 Location filed File #99053
 Monument Found 1/2" OD IP, down 1.4', also
NE & NW 1978 witnesses, add the following:
P. Pole S10°E, 93.61'*
10" W. Oak S45°W, 108.71'*
*distance to double head nail

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____
CERTIFICATE - AL WELLE - MINN DOT - 1978
found 2 1/2" capped pipe (down 12"). TIES:
10" JACK PINE NNW 60.80'; Foundation of HOUSE
NE 128.20'; 12" White Oak SW 94.63'.
Doc. #240560

Mar 2003 B. Givna #17253
Cert. of Surv. shows Mon. Found

1999 - C of S (LANDECKER) indicates
Iron mon. fnd. impl.

July 1905 N.W. Hicks
Trap rd order indicates corner