


Index No. A-12,13

CASS COUNTY LAND CORNER RECORD

T. 138 R. 31 M. 5TH Coordinates: X _____ Y _____

WC 70 Corner common to sections 34-138-31 AND 33-34-139-31



○ = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed AUG. 1865, TB WALKER
Original monument POST 7.50 CH. WEST

Original Evidence Found

Year of search _____ By _____
Monument found _____

Bearing Trees

Species	<u>B. OAK</u>	<u>W. PINE</u>	_____	_____
Diameter	<u>14"</u>	<u>20"</u>	_____	_____
Bearing	<u>N 39° W</u>	<u>S 40° W</u>	_____	_____
Distance	<u>81 Ks</u>	<u>78 Ks</u>	_____	_____

Original Bearing Trees Found

Species	_____	_____	_____	_____
Diameter	_____	_____	_____	_____
Bearing	_____	_____	_____	_____
Distance	_____	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 1915 By J.W. CURD
Location filed RECORDER, CCSO
Monument COUNTY SECTION SUBDIVISION
SET 2 1/4" X 48" I.M. 297' WEST OF
CORNER POSITION IN POND

Evidence of Subsequent Corner Restoration

Year of search 1981 By WELLE, MN/DOT
CERTIFIED WITNESS CORNERS
342.78 EAST AS DOC # 262936 \$
186.39 SOUTH AS DOC. # 262934

Bearing Trees, Reference Objects

Species	_____	_____	_____	_____
Diameter	_____	_____	_____	_____
Bearing	_____	_____	_____	_____
Distance	_____	_____	_____	_____

Bearing Trees, Reference Objects

Species	_____	_____	_____	_____
Diameter	_____	_____	_____	_____
Bearing	_____	_____	_____	_____
Distance	_____	_____	_____	_____

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed _____
Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

Remonumentation certificate prepared _____ By _____

Filed at _____ Date _____