Index No. R21

CASS COUNTY LAND CORNER RECORD

T. 138 R. 32 M. 5TH Coordinates: X _____ Y _____

NE 26 Corner common to sections 23, 24, 25, 26



EXISTING SURVEYS

Original Government Survey

Year surveyed 1870

Original monument Post

Original Evidence Found

Year of search _____ By _____

Monument found _____

Bearing Trees

Species	N. Pine	N. Pine	N. Pine	N. Pine
Diameter	20"	8"	20"	24"
Bearing	N30E	S25½W	N73½W	S36½E
Distance	20 LKS	20 LKS	15 LKS	43 LKS

Original Bearing Trees Found

Species				
Diameter				
Bearing				
Distance				

Subsequent Corner Restoration

Year surveyed 1919 By E.B. Horst

Location filed County Book "C" P. 159

Monument Fnd NE & SW Stumps of Govt Bits and NW & SE Stumps Badly Burned. Set Wood Post in Mound of Stone

Evidence of Subsequent Corner Restoration

Year of search 8/01 By MnDOT

Found iron pipe with cap, 3' above ground, near intersection of trails.

Bearing Trees, Reference Objects

Species				
Diameter				
Bearing				
Distance				

Bearing Trees, Reference Objects

N. Pine	N. Pine	N. Pine	N. Pine
8"	10"	18"	18"
ENE	SSE	WNW	NW
59.00'*	4.37'*	35.01'*	43.89'*

* distance to SRP

(R-21)

Subsequent Corner Restoration

Year surveyed 12/04 By CCSO

Location filed # 2004.083

Monument Found 2" ODIP over 1 3/4" IP with lead plug in top, up 2.5', several rocks around base of pipe. Find MnDot witness as follows:

18" N. Pine N15°E, 43.89'

8" N. Pine S80°E, 59.00'

10" N. Pine S32°W, 4.37'

18" N. Pine N60°W, 35.01'

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

Remonumentation certificate prepared _____ By _____

Filed at _____ Date _____