


Index No. X17

CASS COUNTY LAND CORNER RECORD

T. 139 R. 29 M. 5TH Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_  
E 1/4 34 Corner common to sections 34, 35



○ = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1865  
Original monument Post

Original Evidence Found

Year of search \_\_\_\_\_ By \_\_\_\_\_  
Monument found \_\_\_\_\_

Bearing Trees  
Species N. Pine N. Pine  
Diameter 12" 10"  
Bearing N43 1/2 E N81 W  
Distance 11 LKS 14 LKS

Original Bearing Trees Found

Species \_\_\_\_\_  
Diameter \_\_\_\_\_  
Bearing \_\_\_\_\_  
Distance \_\_\_\_\_

Subsequent Corner Restoration

Year surveyed 3/1918 By H. Curo  
Location filed Roll 13, BK 202, Pg 22  
Monument Cor. Sets West 69.40 feet Mark  
new BT'S

Evidence of Subsequent Corner Restoration

Year of search 4/1937 By J. Curo  
Roll 13, BK 202, Pg 145, ran old  
line set RIR spike at 26.40' for  
Approx. Corner.

Bearing Trees, Reference Objects

Species J.P. J.P.  
Diameter 6" 10"  
Bearing N54°28'W N32°20'E  
Distance 49.05' 50.00'

Bearing Trees, Reference Objects

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Subsequent Corner Restoration

Year surveyed 6/05 By CCSO  
Location filed #2000, 048  
Monument Set Aluminum County Man.  
from 1910 witness trees, 35' E  
North of Ash swamp.  
8" Balsam N44°E, 29.36'\*  
6" Maple S45°E, 25.83'\*  
8" Maple S61°W, 23.83'\*  
\*distance to double head nail

Evidence of Subsequent Corner Restoration Found

Year of search \_\_\_\_\_ By \_\_\_\_\_

Remonumentation certificate prepared \_\_\_\_\_

By \_\_\_\_\_

Filed at \_\_\_\_\_

Date \_\_\_\_\_

(X-17)