


Index No. \_\_\_\_\_

CASS COUNTY LAND CORNER RECORD

T. \_\_\_\_\_ R. \_\_\_\_\_ M. \_\_\_\_\_ Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_

Corner common to sections \_\_\_\_\_



EXISTING SURVEYS

Original Government Survey

Original Evidence Found

Year surveyed \_\_\_\_\_

Year of search \_\_\_\_\_ by \_\_\_\_\_

Original monument \_\_\_\_\_

Monument found \_\_\_\_\_

Bearing Trees

Original Bearing Trees Found

Species \_\_\_\_\_

Species \_\_\_\_\_

Diameter \_\_\_\_\_

Diameter \_\_\_\_\_

Bearing \_\_\_\_\_

Bearing \_\_\_\_\_

Distance \_\_\_\_\_

Distance \_\_\_\_\_

Subsequent Corner Restoration

Evidence of Subsequent Corner Restoration

Year surveyed \_\_\_\_\_ By \_\_\_\_\_

Year of search \_\_\_\_\_ By \_\_\_\_\_

Location filed: \_\_\_\_\_

Location filed: \_\_\_\_\_

Monument: \_\_\_\_\_

Monument: \_\_\_\_\_

Bearing Trees, Reference Objects

Bearing Trees, Reference Objects

Species \_\_\_\_\_

Species \_\_\_\_\_

Diameter \_\_\_\_\_

Diameter \_\_\_\_\_

Bearing \_\_\_\_\_

Bearing \_\_\_\_\_

Distance \_\_\_\_\_

Distance \_\_\_\_\_

Subsequent Corner Restoration

Evidence of Subsequent Corner Restoration Found

Year surveyed \_\_\_\_\_ By \_\_\_\_\_

Year of search \_\_\_\_\_ By \_\_\_\_\_

Location filed: \_\_\_\_\_

Location filed: \_\_\_\_\_

Monument: \_\_\_\_\_

Monument: \_\_\_\_\_

Index No. \_\_\_\_\_

CASS COUNTY LAND CORNER RECORD

T. \_\_\_\_\_ R. \_\_\_\_\_ M. \_\_\_\_\_ Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_

Page \_\_\_\_\_ of \_\_\_\_\_

Corner common to sections \_\_\_\_\_


Subsequent Corner Restoration

Evidence of Subsequent Corner Restoration Found

Year surveyed \_\_\_\_\_ By \_\_\_\_\_  
Location filed:  
Monument:

Year of search \_\_\_\_\_ By \_\_\_\_\_  
Location filed:  
Monument:

T. 139 R. 30 M. 5th Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_  
NE 17 Corner common to sections 8, 9, 16, 17



EXISTING SURVEYS

**Original Government Survey**

Year surveyed 1865  
Original monument Post

Species	Bearing	Tree
<u>N. Pine</u>	<u>BL. Pine</u>	<u>N. Pine</u>
Diameter <u>24"</u>	<u>15"</u>	<u>20"</u>
Bearing <u>N75W</u>	<u>S40W</u>	<u>N21E</u>
Distance <u>324 LKS</u>	<u>433 LKS</u>	<u>1282 LKS</u>

**Original Evidence Found**

Year of search \_\_\_\_\_ By \_\_\_\_\_  
Monument found \_\_\_\_\_

**Original Bearing Trees Found**

Species \_\_\_\_\_  
Diameter \_\_\_\_\_  
Bearing \_\_\_\_\_  
Distance \_\_\_\_\_

**Subsequent Corner Restoration**

Year surveyed 1907 By JOHN CURD  
Location filed COUNTY SURVEY RECORD BOOK "A" P138-139  
Monument Found 24" N. Pine N75W 213.8', 15" Bl. Pine S40W 285.8'. Set 8x8x36" concrete post

**Evidence of Subsequent Corner Restoration**

Year of search 1914 By Gaymen  
microfilm - roll 115 BK92 P. 18  
start east from true corner

**Bearing Trees, Reference Objects**

Species \_\_\_\_\_  
Diameter \_\_\_\_\_  
Bearing \_\_\_\_\_  
Distance \_\_\_\_\_

**Bearing Trees, Reference Objects**

\_\_\_\_\_

**Subsequent Corner Restoration**

Year surveyed 4/2001 By CCSO  
Location filed file # 2000.022  
Monument Found 60d spike, down 0.8', on 2 & 2, 1983 MN/DOT witness in good condition, add the following:  
Tel. Ped. Post S61°W, 61.20' to dbl hd nail  
Oct. 2000, B. Grivna #17253  
Cert. of Survey shows monument found

**Evidence of Subsequent Corner Restoration Found**

Year of search \_\_\_\_\_ By \_\_\_\_\_

Certificate - Jim Nielsen - Minn DOT - 1983  
Found bottom part of 8x8 concrete monument down 24". Set MN DOT cast iron monument (down .2'). Ties: Power Pole N55W 67.32'; Telephone pole N45E 42.13'; 10" Jack Pine S35E 90.05'.  
Doc # 267947

July 1919; Twp rd order shows corners previously established