


T. 140 R. 25 M. 5TH Coordinates: X _____ Y _____

NE 10 Corner common to sections 2, 3, 10, 11



EXISTING SURVEYS

Original Government Survey
 Year surveyed 1867
 Original monument POST

Original Evidence Found
 Year of search _____ By _____
 Monument found _____

Species	Bearing		Trees
	BL. PINE	BL. PINE	
Diameter	<u>15"</u>	<u>5"</u>	<u>SPRUCE</u>
Bearing	<u>N35 1/2 E</u>	<u>S85 E</u>	<u>8"</u>
Distance	<u>7 LKS.</u>	<u>16 LKS</u>	<u>41 LKS</u>

Original Bearing Trees Found

Species	Diameter	Bearing	Distance

Subsequent Corner Restoration
 Year surveyed 1912 By HARRY S. TIDD.
 Location filed COUNTY SURVEY RECORD BOOK "A" P 552-555
 Monument SET CORNER FROM OLD GOVT B.T.S. 1920, E.B. HORST, COUNTY BOOK "C" P 533 FWO

Evidence of Subsequent Corner Restoration
 Year of search 1937 By CCC
Washburn Lake - BK # 4 P. 22
at 5260 from E. Set approx cor in center of road

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance
<u>BIRCH STUMP</u>	<u>12"</u>	<u>NE</u>	<u>47.80'</u>
<u>J. PINE STUMP</u>	<u>8"</u>	<u>SE</u>	<u>62.50'</u>

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance

Subsequent Corner Restoration

Year surveyed _____ By _____
 Location filed _____
 Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____
Certificate - Gary Stevenson - 1984
Doc. # 275703
Set County Cast Iron monument. Ties:
Power Pole N42E 49.55'; 16" JACK PINE
S85 E 118.80'; 6" Twin Birch S40E 110.88'
1998 - CCSD - Found CIM, add nails
to 1984 witnesses. 5.5' E. of 2
18" J. Pine, S85°E, 118.75*
8" Twin Birch, S35°E, 110.04*
6" Spruce, S73°W, 78.70*
8" J. Pine, N80°E, 92.99*
* distance to double head nail
1905, Twp Road Order, C. Taylor,
Surveyors Report indicates corner
post.