


T. 140 R. R7 M. 5th Coordinates: X _____ Y _____
E14 16 Corner common to sections 15, 16



○ = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1873
Original monument Post

Bearing Trees	
Species <u>Ash</u>	<u>W. Pine</u>
Diameter <u>5"</u>	<u>20"</u>
Bearing <u>N73-30W</u>	<u>S1E</u>
Distance <u>31 LKS</u>	<u>39 LKS</u>

Original Evidence Found

Year of search _____ By _____
Monument found _____

Original Bearing Trees Found

Species _____	_____
Diameter _____	_____
Bearing _____	_____
Distance _____	_____

Subsequent Corner Restoration

Year surveyed 1909 By John Cure
Location filed COUNTY SURVEY RECORD BOOK 'A' P308-312
Monument END ORLG B.T. DOWN: 20" W. PINE S1E 25.7'
SET 4x4x48" MAPLE POST

Bearing Trees, Reference Objects	
Species <u>W. Pine Stump</u>	<u>W. Pine Stump</u>
Diameter <u>26"</u>	<u>30"</u>
Bearing <u>N78-30E</u>	<u>S33E</u>
Distance <u>57.80'</u>	<u>58.65'</u>

Evidence of Subsequent Corner Restoration

Year of search 1911 By Harry Todd
microfilm - roll 115 BK 93 P. 14
End corner previously established by Cure

Bearing Trees, Reference Objects

_____	_____
_____	_____
_____	_____
_____	_____

L-13

Subsequent Corner Restoration

Year surveyed Mar 1998 By C.C. Land Dept. - A.R., C.L.
Location filed _____
Monument Man found exc cond.

Remonumentation certificate prepared _____
Filed at _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____
1991 Cert. Filed by David Landecker
Doc # 329218
Set 2" square County tubular monument
with 3" stamped aluminum cap. Ties:
5" Ash N54E 22.69'; 10" Basswood S57E
50.27'; 5" Maple S40E 35.03'; 6" Maple
S8W 32.07'.

By _____
Date _____