


T. 140 R. 28 M. 5TH Coordinates: X _____ Y _____
NE 1 Corner common to sections 1 AND 6 - 140-27



EXISTING SURVEYS

Original Government Survey

Year surveyed 1863
Original monument POST

Species	W. Pine	Bearing	Trees
Diameter	<u>14"</u>	<u>4"</u>	
Bearing	<u>S30E</u>	<u>S76W</u>	
Distance	<u>20 LKS</u>	<u>140 LKS.</u>	

Original Evidence Found

Year of search _____ By _____
Monument found _____

Original Bearing Trees Found

Species			
Diameter			
Bearing			
Distance			

Subsequent Corner Restoration

Year surveyed 1912 By A.W. MOULSTER
Location filed COUNTY SURVEY RECORD BOOK A' P 519
Monument Find old GOVT BIT: 14" W. PINE S30E
20 LKS ALSO OLD STATE SET STAKE ANOTHER STAKE
2.10' SOUTH FOR TREE CLOSING CORNER
1910 - also on microf. film - Roll 105 BK 50 P. 20-21
" " " " Roll 105 BK 69 P. 65, 69
Bearing Trees, Reference Objects

Species			
Diameter			
Bearing			
Distance			

Evidence of Subsequent Corner Restoration

Year of search 1920 By BEN CLARK
COUNTY BOOK D' P 185 FIND POINT OF OLD STAKE
AND GOVT BIT: 14" W. PINE S30E (DOWN)
SET 3X30" IRON POST

Bearing Trees, Reference Objects

A-25

Subsequent Corner Restoration

Year surveyed 1937 By CCC
Location filed Washburn Lake - BK # 5 P. 55
Monument APPROX Cor. in center of fields E-WIS

Corner GPS CCSO 7/21/02
CCSO Ed. 1" ODIP, Flush, on ♀ ♀

Evidence of Subsequent Corner Restoration Found

Year of search SEPT. 2000 By CCSO
Find in place; 1" ODIP. ♀ CSAH 7 E 2.5' W
♀ N. Rice Lk. Rd. NE.

REF. TIES:

<u>P. Pole</u>	<u>N 21° W</u>	<u>65.34'</u>
<u>Signpost</u>	<u>N 62° E</u>	<u>44.87'</u>
<u>11" W. oak</u>	<u>S 49° E</u>	<u>145.19'</u>
<u>10" W. Pine</u>	<u>S 44° W</u>	<u>64.03'</u>
<u>* dist. to dbl. hd. nail</u>		

Remonumentation certificate prepared _____

Filed at _____

By _____

Date _____