


Index No. R3

CASS COUNTY LAND CORNER RECORD

T. 140 R. 28 M. 5TH Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_  
N1/4 30 Corner common to sections 19, 30



EXISTING SURVEYS

Original Government Survey

Year surveyed 1870

Original monument Post

Bearing Trees

Species	<u>W. PINE</u>	<u>W. PINE</u>	_____
Diameter	<u>16"</u>	<u>20"</u>	_____
Bearing	<u>N10E</u>	<u>S30W</u>	_____
Distance	<u>18 LKS</u>	<u>21 LKS</u>	_____

Original Evidence Found

Year of search \_\_\_\_\_ By \_\_\_\_\_

Monument found \_\_\_\_\_

Original Bearing Trees Found

Species	_____	_____	_____
Diameter	_____	_____	_____
Bearing	_____	_____	_____
Distance	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 1916 By E. P. ROBERT

Location filed COUNTY SURVEY RECORD BOOK 8 P. 125

Monument FIND OLD STAKE AND OLD GUYOT P.T. STUMPS!  
16" W. PINE N10E 78 LKS, 20" W. PINE S30W 21 LKS  
SET NEW STAKE  
also on microfilm - roll 105 BK 56 P. 15

Bearing Trees, Reference Objects

Species	<u>BASSWOOD</u>	<u>MAPLE</u>	_____
Diameter	<u>18"</u>	<u>10"</u>	_____
Bearing	<u>N52E</u>	<u>S41E</u>	_____
Distance	<u>56.20'</u>	<u>30.70'</u>	_____

Evidence of Subsequent Corner Restoration

Year of search 1947 By HAROLD LUD

COUNTY BOOK "D" P. 407 RESET CORNER FROM PREVIOUS SURVEYS

Bearing Trees, Reference Objects

	<u>ROAK</u>	<u>BIRCH</u>	_____
	<u>12"</u>	<u>6"</u>	_____
	<u>N55-14W</u>	<u>S53-47W</u>	_____
	<u>42.55'</u>	<u>43.30'</u>	_____

Subsequent Corner Restoration

Year surveyed 1956 By John Howard

Location filed Map's notes of DNR Access

Monument iron pipe

Evidence of Subsequent Corner Restoration Found

Year of search \_\_\_\_\_ By \_\_\_\_\_

PLAT - KOWFELDT'S BEACH  
JOHN E. HOWARD 1956

PLAT - HIGHWOOD  
R. F. SCHNEIDER 1968