


Index No. E5

CASS COUNTY LAND CORNER RECORD

T. 140 R. 30 M. 5TH Coordinates: X _____ Y _____
NE 7 Corner common to sections 5, 6, 7, 8



○ = Corner

EXISTING SURVEYS

Original Government Survey
Year surveyed 1865
Original monument POST

Original Evidence Found
Year of search _____ By _____
Monument found _____

	Bearing Trees		
Species	<u>DEAD W. PINE</u>	<u>W. BIRCH</u>	<u>ASPEN</u>
Diameter	<u>30"</u>	<u>4"</u>	<u>5"</u>
Bearing	<u>N35E</u>	<u>S54W</u>	<u>S72E</u>
Distance	<u>83 LKS</u>	<u>41 LKS</u>	<u>36 LKS</u>

Original Bearing Trees Found			
Species	_____	_____	_____
Diameter	_____	_____	_____
Bearing	_____	_____	_____
Distance	_____	_____	_____

Subsequent Corner Restoration
Year surveyed 1973 By JOHN GREENE
Location filed COUNTY RESURVEY E-35
Monument 2x4B' CAPPED I.P.
1965, R.F. SCHNEIDER, BOOK "D" P.448 FWD I.P. (NEW TIES)

Evidence of Subsequent Corner Restoration
Year of search _____ By _____

Bearing Trees, Reference Objects			
Species	<u>N. PINE</u>	<u>W. OAK</u>	<u>W. OAK</u>
Diameter	<u>18"</u>	<u>6"</u>	<u>12"</u>
Bearing	<u>N88E</u>	<u>N78W</u>	<u>N30E</u>
Distance	<u>117.8'</u>	<u>26.55'</u>	<u>27.0'</u>

Bearing Trees, Reference Objects			
Species	_____	_____	_____
Diameter	_____	_____	_____
Bearing	_____	_____	_____
Distance	_____	_____	_____

E-5

Subsequent Corner Restoration
Year surveyed 8/03 By CCSO
Location filed #2003.059
Monument Found 2 1/2" ODIP w/plumber cap, up 1.0', NE corner of Logging. Add the following:

14" W. Oak, N30°E, 27.40'* (1981)
8" W. Oak, S20°E, 54.98'*
*distance to double head nail

Evidence of Subsequent Corner Restoration Found
Year of search _____ By _____
Certificate - Jim Nielsen - Minn DOT - 1983
Doc. # 267921
Found 2 1/2" capped pipe (up 1.0'). TIES:
10" Twin White Oak N78W 26.60'; 14"
White Oak N30E 27.40'; 20" Norway
Pine N88E 118.10'.

Remonumentation certificate prepared _____
Filed at _____

By _____
Date _____