


Index No. 25

CASS COUNTY LAND CORNER RECORD

T. 140 R. 30 M. 5TH Coordinates: X _____ Y _____
E 1/4 18 Corner common to sections 17, 18 W.C. 86 CH. NORTH



○ = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1865
Original monument POST W.C. 86 LKS NORTH

Original Evidence Found

Year of search _____ By _____
Monument found _____

Species	Bearing	Trees
<u>N. Pine</u>	<u>Aspen</u>	
Diameter <u>15"</u>	<u>4"</u>	
Bearing <u>N75W</u>	<u>N35E</u>	
Distance <u>29 LKS.</u>	<u>48 LKS</u>	

Original Bearing Trees Found

Species	Diameter	Bearing	Distance

Subsequent Corner Restoration

Year surveyed 1915 By JOHN CURD
Location filed COUNTY RESURVEY E-36
Monument 2 1/4 x 4 1/8 1 M'S, W.C.S, 56.8' NORTH 140' WEST
1921- E.B. HORST - COUNTY RESURVEY E-36 W.C. 56.8' N AND
1318.95' EAST
BOOK "C" P. 437 IRON MONUMENT

Evidence of Subsequent Corner Restoration

Year of search _____ By _____

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed _____
Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

Certificate - Jim Nreksen - Minn DOT 1983
Doc. # 267927
Found 2" capped pipe witness corner 140'
WEST of corner location. TIES: 24" White
Oak N69°14'W 77.00'; 10" Ash N79°50'E
33.35';

Remonumentation certificate prepared _____

By _____

Filed at _____

Date _____