


Index No. N21

CASS COUNTY LAND CORNER RECORD

T. 140 R. 30 M. 5TH Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_  
NE 23 Corner common to sections 13, 14, 23, 24



EXISTING SURVEYS

Original Government Survey

Year surveyed 1865  
Original monument POST

Original Evidence Found

Year of search \_\_\_\_\_ By \_\_\_\_\_  
Monument found \_\_\_\_\_

	Bearing	Trees		
Species	<u>DEAD PINE</u>	<u>DEAD PINE</u>	<u>DEAD PINE</u>	<u>DEAD PINE</u>
Diameter	<u>12"</u>	<u>8"</u>	<u>8"</u>	<u>9"</u>
Bearing	<u>N48 1/2 E</u>	<u>N5W</u>	<u>S68W</u>	<u>S10E</u>
Distance	<u>46 LKS</u>	<u>34 LKS</u>	<u>35 LKS</u>	<u>34 LKS</u>

Original Bearing Trees Found

Species	_____	_____	_____	_____
Diameter	_____	_____	_____	_____
Bearing	_____	_____	_____	_____
Distance	_____	_____	_____	_____

O = Corner

Subsequent Corner Restoration

Year surveyed 1907 JULY By JOHN CURD  
Location filed COUNTY BOOK "B" P433-441 B7S CONE  
Monument FIND STAKE SET BY CANFIELD (TESTIMONY)  
1965, R.F. SCHNEIDER, COUNTY BOOK "D" P443 FIND NAIL IN  
G. HWY (NEW TIES)

Evidence of Subsequent Corner Restoration

Year of search \_\_\_\_\_ By \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Bearing Trees, Reference Objects

Species	<u>W. OAK</u>	<u>J. PINE</u>	<u>POWER POLE</u>
Diameter	<u>8"</u>	<u>14"</u>	_____
Bearing	<u>S7E</u>	<u>S51 1/2 W</u>	<u>N35W</u>
Distance	<u>70.6'</u>	<u>165.0'</u>	<u>105.85'</u>

Bearing Trees, Reference Objects

_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

Subsequent Corner Restoration

Year surveyed \_\_\_\_\_ By \_\_\_\_\_  
Location filed \_\_\_\_\_  
Monument \_\_\_\_\_

Evidence of Subsequent Corner Restoration Found

Year of search \_\_\_\_\_ By \_\_\_\_\_

Remonumentation certificate prepared \_\_\_\_\_ By \_\_\_\_\_

Filed at \_\_\_\_\_ Date \_\_\_\_\_